ies and
uses only properly trained personnel.*
Refer to the Recommendation on conditions for the approval of servicing stations for inflatable liferafts, adopted by the Organization by resolution A.693(17).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
---CHUNK---
SOURCE: MSC.36(63).pdf
Refer to the Recommendation on conditions for the approval of servicing stations for inflatable liferafts, adopted by the Organization by resolution A.693(17).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 90
8.9.8
8.9.9
8.10
8.10.1
All repairs and maintenance of inflated rescue boats should be carried out in accordance with the manufacturer's instructions. Emergency repairs may be carried out on board the craft; however, permanent repairs should be effected at an approved servicing station.
Periodic servicing of hydrostatic release units
Hydrostatic release units should be serviced:
.1 at intervals not exceeding 12 months, provided where in any case this is impracticable, the Administration may extend this period by one 'month;
.2 at a servicing station which is competent to service them, maintains proper servicing facilities and uses only properly trained personnel.
Survival craft and resc ue boat~
All craft should carry:
.1 survival craft with sufficient capacity as will accommodate
---CHUNK---
SOURCE: MSC.36(63).pdf
maintains proper servicing facilities and uses only properly trained personnel.
Survival craft and resc ue boat~
All craft should carry:
.1 survival craft with sufficient capacity as will accommodate not less than 100% of the total number of persons the craft is certified to carry, subject to a minimum of two such survival craft being carried;
.2 in addition, survival craft with sufficient aggregate capacity to accommodate not less than 10% of the total number of persons the craft is certified to carry;
.3 in the event of anyone survival craft being lost or rendered unserviceable, sufficient survival craft to accommodate the total number of persons the craft is certified to carry;
.4 at least one rescue boat for retrieving persons from the water, but not less than one such boat on each side when the craft is certified to carry more than 450 passengers;
.5 craft of less than 20 m in length may be exempted from carrying a rescue boat, provided the craft meets all of the following requirements:
.5.1
.5.2
.5.3
the craft is arranged to allow a helpless person to be recovered from the water;
recovery of the helpless person can be observed from the
---CHUNK---
SOURCE: MSC.36(63).pdf
carrying a rescue boat, provided the craft meets all of the following requirements:
.5.1
.5.2
.5.3
the craft is arranged to allow a helpless person to be recovered from the water;

recovery of the helpless person can be observed from the navigating bridge; and
the craft is sufficiently manoeuvrable to close and recover persons ill the worst intended conditions.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 8.10.2
MSC 62/23/Add.2
ANNEX 18
Page 91
.6 notwithstanding prov1s1ons of .4 and .5 above, craft should carry sufficient rescue boats to ensure that, in providing for abandonment by the total number of persons the craft is certified to carry:
.6.1 not more than nine of the liferafts provided in accordance with 8.10.1.1 are marshalled by each rescue boat; or
.6.2 if the Administration is satisfied that the rescue boats are capable of towing a pair of such liferafts simultaneously, not more than 12 of the liferafts provided in accordance with 8.10.1.1 are marshalled by each rescue boat; and
.6.3 the craft can be evacuated within the time specified in 4.8.
---CHUNK---
SOURCE: MSC.36(63).pdf
boats are capable of towing a pair of such liferafts simult