solution A.605(15).
** Refer to the Recommendation on performance standards for survival craft radar transponders for use in search and rescue operations, adopted by the Organization by resolution A.697(17).
WI1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 84
8.2.2
8.2.3
8.2.3.1
8.2.3.2
Craft should be provided with the following on-board communications and alarm systems:
.1 an emergency means comprising either fixed or portable equipment or both for two-way communications between emergency control stations, muster and embarkation stations and strategic positions on board; and
.2 a general emergency alarm system complying with the requirements of regulation III/50 of the Convention to be used for summoning passengers and crew to muster stations and to initiate the actions included in the muster list. The system should be supplemented by either a public address system or other suitable means of communication. The systems should be
---CHUNK---
SOURCE: MSC.36(63).pdf
for summoning passengers and crew to muster stations and to initiate the actions included in the muster list. The system should be supplemented by either a public address system or other suitable means of communication. The systems should be operable from the operating compartment.
Signalling eguipment
All craft should be provided with a portable daylight signalling lamp which is available for use in the operating compartment at all times and which is not dependent on the craft's main source of electrical power.
Craft should be provided with not less than 12 rocket parachute flares, complying with the requirements of regulation 111/35 of the Convention, stowed in or near the operating compartment.
8.3 Personal liLe - saying appliances
8.3.1 Where passengers or crew have access to exposed decks under normal operating conditions, at least one lifebuoy on each side of the c 'raft capable of quick release from the control compartment and from a position at or near where it is stowed, should be provided with a self-igniting light and a self-activating smoke signal. The positioning and securing arrangements of the self-activating smoke
---CHUNK---
SOURCE: MSC.36(63).pdf
a position at or near where it is stowed, should be provided with a self-igniting light and a self-activating smoke signal. The positioning and securing arrangements of the self-activating smoke signal should be such that it cannot be released or activated solely by the accelerations produced by collisions or groundings.
8.3.2 At least one lifebuoy should be provided adjacent to each normal exit from the craft and on each open deck to which passengers and crew have access, subject to a minimum of two being installed.
8.3.3 Lifebuoys fitted adjacent to each normal exit from the craft should be fitted with buoyant lines of at least 30 m in length.
8.3.4
8.3.5
Not less than half the total
with self-igniting lights.
self-igniting lights should
accordance with 8.3.3.
number of lifebuoys should be fitted
However, the lifebuoys provided with
not include those provided with lines in
A lifejacket complying with the requirements of regulation 111/32.1 or 111/32.2 of the Convention should be provided for every person on board the craft and, in addition:
.1 a number of lifejackets suitable for children equal to at
---CHUNK---
SOURCE: MSC.36(63).pdf
A lifejacket complying with the requirements of regulation 111/32.1

or 111/32.2 of the Convention should be provided for every person on board the craft and, in addition:

.1 a number of lifejackets suitable for children equal to at least 10% of the number of passengers on board should be provided or such greater number as may be required to provide a lifejacket for each child;

W/l687n/pp/EWP

RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FO