learance from the
propeller or waterjet and steeply overhanging portions of the hull.
Refer to Symbols related to life-saving appliances and arrangements, adopted by the Organization by resolution A.760(18).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT n
8.6.7
8.6.8
8.6.9
8.6.10
8.6.11
8.6.12
8.7
8.7.1
8.7.2
MSC 62/23/Add.2
ANNEX 18
Page 87
During preparation and launching, the survival craft and the area of water into which it is to be launched should be adequately
---CHUNK---
SOURCE: MSC.36(63).pdf
8.6.7
8.6.8
8.6.9
8.6.10
8.6.11
8.6.12
8.7
8.7.1
8.7.2
MSC 62/23/Add.2
ANNEX 18
Page 87
During preparation and launching, the survival craft and the area of water into which it is to be launched should be adequately illuminated by the lighting supplied from the main and emergency sources of electrical power required by chapter 12.
Means should be available to prevent any discharge of water on to survival craft when launched.
Each survival craft should be stowed:
.1 so that neither the survival craft nor its stowage arrangements will interfere with the operation of any other survival craft or rescue boat at any other launching station;
.2 in a state of continuous readiness:
.3 fully equipped; and
.4 as far as practicable, in a secure and sheltered position and protected from damage by fire and explosion.
Every liferaft should be stowed with its painter permanently attached to the craft and with a float free arrangement complying with the requirements of regulation III/38.6 of the Convention so that, as far as practicable, the liferaft floats free and, if inflatable, inflates automatically should the high speed craft sink.
---CHUNK---
SOURCE: MSC.36(63).pdf
with the requirements of regulation III/38.6 of the Convention so that, as far as practicable, the liferaft floats free and, if inflatable, inflates automatically should the high speed craft sink.
Rescue boats should be stowed:
.1 in a state of continuous readiness for launching in not more than 5 min;
.2 in a position suitable for launching and recovery; and
.3 so that neither the rescue boat nor its stowage arrangements will interfere with the operation of survival craft at any other launching station.
Rescue boats and survival craft should be secured and fastened to the deck so that they at least withstand the loads likely to arise due to a defined horizontal collision load for the actual craft, and the vertical design load at the stowage position.
Survival craft and rescue boat embarkation and recovery arrangements
Embarkation stations should be readily accessible from accommodation and work areas. If the designated muster stations are other than the passenger spaces, the muster stations should be readily accessible from the passenger spaces, and the embarkation stations

should be readily accessible from the muster stations.
---CHUNK---
SOURCE: MSC.36(63).pdf
the passenger spaces, the muster stations should be readily accessible from the passenger spaces, and the embarkation stations should be readily accessible from the muster stations.
Evacuation routes, exits and embarkation points should comply with the requirements of 4.7.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 88
8.7.3
8.7.4
8.7.5
8.7.6
8.7.7
8.8
8.9
8.9.1
8.9.2
Alleyways, stairways and exits giving access to the muster and embarkation stations should be adequately illuminated by lighting supplied from the main and emergency source of electrical power required by chapter 12.
Where davit-launched survival craft are not fitted, MES or equivalent means of evacuation should be provided in order to avoid persons entering the water to board survival craft. Such MES or equivalent means of evacuation should be so designed as