ll be
clearly marked.

_____

* Refer to the Performance standards for survival craft radar transponders for use in search a
nd
rescue operations, adopted by the Organization by resolution A.802(19).■
CHAPTER XII
ADDITIONAL SAFETY MEASURES FOR BULK CARRIERS
9 The following new regulations 12 and 13 are added after existing regulation 11:
■Regulation 12
Hold, ballast and dry space water level detectors
(This regulation applies to bulk carriers regardless of their date of construction)
1 Bulk carriers shall be fitted with water level detectors:
RESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL
---CHUNK---
SOURCE: MSC.134(76).pdf
1 Bulk carriers shall be fitted with water level detectors:
RESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL
CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDEDMSC 76/23/Add.1
ANNEX 3
Page 7
I:\MSC\76\23-ADD.1.DOC
.1 in each cargo hold, giving audible and visual alarms, one when the water
level above the inner bottom in any hold reaches a height of 0.5 m and
another at a height not less than 15% of the depth of the cargo hold but not
more than 2 m. On bulk carriers to which regulation 9.2 applies, detectors
with only the latter alarm need be installed. The water level detectors shall
be fitted in the aft end of the cargo holds. For cargo holds which are used
for water ballast, an alarm overriding de vice may be installed. The visual
alarms shall clearly discriminate be tween the two different water levels
detected in each hold;
.2 in any ballast tank forward of the collision bulkhead required by
regulation II-1/11, giving an audible a nd visual alarm when the liquid in
the tank reaches a level not exceeding 10% of the tank capacity. An alarm
---CHUNK---
SOURCE: MSC.134(76).pdf
detected in each hold;
.2 in any ballast tank forward of the collision bulkhead required by
regulation II-1/11, giving an audible a nd visual alarm when the liquid in
the tank reaches a level not exceeding 10% of the tank capacity. An alarm
overriding device may be installed to be activated when the tank is in use;
and
.3 in any dry or void space other than a chain cable locker, any part of which
extends forward of the foremost cargo hold, giving an audible and visual
alarm at a water level of 0.1 m above the deck. Such alarms need not be
provided in enclosed spaces the volume of which does not exceed 0.1% of
the ship■s maximum displacement volume.
2 The audible and visual alarms specified in paragraph 1 shall be located on the
navigation bridge.
3 Bulk carriers constructed before 1 July 2004 shall comply with the requirements
of this regulation not later than the date of the annual, intermediate or renewal survey of
the ship to be carried out after 1 July 2004, whichever comes first.
Regulation 13
Availability of pumping systems
(This regulation applies to bulk carriers regardless of their date of construction)
---CHUNK---
SOURCE: MSC.134(76).pdf
the ship to be carried out after 1 July 2004, whichever comes first.
Regulation 13
Availability of pumping systems
(This regulation applies to bulk carriers regardless of their date of construction)
1 On bulk carriers, the means for draining and pumping ballast tanks forward of the
collision bulkhead and bilges of dry spaces a ny part of which extends forward of the
foremost cargo hold shall be capable of being brought into operation from a readily
accessible enclosed space, the location of which is accessible from the navigation bridge
or propulsion machinery control position without traversing exposed freeboard or
superstructure decks. Where pipes servi ng such tanks or bilges pierce the collision
bulkhead, valve operation by means of remote ly operated actuators may be accepted, as
an alternative to the valve control specifi ed in regulation II-1/1