e present resolution:
(a) Resolution A. 803(19) - Performance Standards for Shipborne VHF Radio Installations Capable of Voice Communication and Digital Selective Calling (Annex 1);
(b) Resolution A.804(19) - Performance Standards for Ship borne MF Radio Installations Capable of Voice Communication and Digital Selective Calling (Annex 2);
(c) Resolution A. 806(1 9) - Performance Standards for Shipborne MFIHF Radio Installations Capable of Voice Communication, Narrow-Band Direct-Printing and Digital Selective Calling (Annex 3); and
(d) Resolution A. 807(19) - Performance Standards for Inmarsat-C Ship Earth Stations Capable of Transmitting and Receiving Direct-Printing Communications (Annex 4);
2. RECOMMENDS Governments to ensure that equipment and systems listed in the present resolution and installed on or after 1 January 2000 conform to the amended performance standard
s
specified in the attached Annexes .
I:\MSC\68\23 -Add.l
---CHUNK---
SOURCE: MSC.68%2868%29.pdf
resolution and installed on or after 1 January 2000 conform to the amended performance standard
s
specified in the attached Annexes .
I:\MSC\68\23 -Add.l
RESOLUTION MSC.68(68)
(adopted on 6 June 1997)
ADOPTION OF AMENDMENTS TO PERFORMANCE STANDARDS
FOR SHIPBORNE RADIOCOMMUNICATION EQUIPMENT MSC 68/23/ Add. 1
ANNEX 10
Page 2
ANNEX 1
AMENDMENTS TO RESOLUTION A.803(19) ~ PERFORMANCE STANDARDS
FOR VHF RADIO INSTALLATIONS CAPABLE OF VOICE COMMUNICATION
AND DIGITAL SELECTIVE CALLING
Modify paragraphs 11.2.5 and 11.2.6 of the Annex, as follows:
".5 facilities to automatically update the ship's position and the time at which the position w
as
determined from a suitable electronic position-fixing aid which may be an integral part of the equipment. For equipment which does not have an integral position-fixing aid, such facilities should include a suitable interface conforming to the appropriate international standard; 1
---CHUNK---
SOURCE: MSC.68%2868%29.pdf
of the equipment. For equipment which does not have an integral position-fixing aid, such facilities should include a suitable interface conforming to the appropriate international standard; 1
.6 means for manual entry of position information and the time at which the position was determined; and"
Add new paragraph 11.2.7 :
".7 means to activate an alarm when no position data is received from the electronic position-fixing aid or, in the case of manual input, the position information is over 4 hours old. Any position information not updated for more than 23 Y2 hours should be erased."
Modify paragraph 11.3.2, as follows:
".3.2 These messages should be stored until readout and should be erased 48 hours after their reception. II
Modify the second sentence of paragraph 11.4, as follows:
"11. 4 ..... The means for initiating a distress alert should be as prescribed in 2.6 to 2.8.
II
IEC 1162
J:\MSC\68\23-Add .l
RESOLUTION MSC.68(68)
(adopted on 6 June 1997)
---CHUNK---
SOURCE: MSC.68%2868%29.pdf
"11. 4 ..... The means for initiating a distress alert should be as prescribed in 2.6 to 2.8.
II
IEC 1162
J:\MSC\68\23-Add .l
RESOLUTION MSC.68(68)
(adopted on 6 June 1997)
ADOPTION OF AMENDMENTS TO PERFORMANCE STANDARDS
FOR SHIPBORNE RADIOCOMMUNICATION EQUIPMENT ANNEX 2
MSC 68/23/ Add . 1
ANNEX 10
Page 3
AMENDMENTS TO RESOLUTION A.804(19) - PERFORMANCE STANDARDS
FOR MF RADIO INSTALLATIONS CAPABLE OF VOICE COMMUNICATION
AND DIGITAL SELECTIVE CALLING
Modify paragraphs 2.4,2 .5 and 2.6 of Part D of the Annex, as follows :

".4 means to display, in plain language with a minimum of 160 characters in two or more lines, the information contained in a received call;
.5 facilities to automatically update the ship's position and the time at which the position was
determined from a suitable electronic position-fixing aid which may be an integral part of the equipment. For equipment which does not have an integral position-fixing aid,
---CHUNK---
SOURCE: MSC.68%2868%29.