to the ship reporting system by voice or by
non-verbal means.
3.1 Format
3.1.1 The information given below is derived from the format-type given in paragraph 2 of the
appendix to resolution A.851(20).
3.2 Content
3.2.1 A short report by voice or by AIS from a sh ip to the shore-based authorities should
contain the following information:
A Name of the ship, call sign or IMO identification number (or MMSI for
transponder reports)
B Date and Time (UTC)
C or D Position (expressed in latitude and longitude or bearing to and distance
from a landmark)
E and F Course and speed of the ship
---CHUNK---
SOURCE: MSC.139(76).pdf
transponder reports)
B Date and Time (UTC)
C or D Position (expressed in latitude and longitude or bearing to and distance
from a landmark)
E and F Course and speed of the ship
3.2.2 A full report from a ship to the shore-ba sed authorities by voice or by non-verbal means
should contain the following information:
I Destination and ETA
L Route information
O Vessel's draught
P Hazardous cargo, class and quantity, if applicable
Q or R Breakdown, damage and/or deficien cies affecting the structure, cargo or
equipment of the ship or any other circumstances affecting normal
navigation in accordance with the provisions of the SOLAS and MARPOL
Conventions
T Contact information of ship's agent or owner
U Ship's deadweight tonnage
W Total number of persons on board
X Miscellaneous remarks, e.g. ice class, amount and nature of bunkers if
over 5000 tons, navigational status
Note:
On receipt of a position message, the system operators will establish the relationship
between the ship's position and the information supplied by the position-fixing equipment
available to them. Information on course and speed will help operators to identify one
---CHUNK---
SOURCE: MSC.139(76).pdf
between the ship's position and the information supplied by the position-fixing equipment
available to them. Information on course and speed will help operators to identify one
ship among a group of ships. This will be achieved automatically if AIS transponder is
used.
All VHF-, telephone-, radar-, AIS- and other relevant information will be recorded and
the records stored for 30 days.
RESOLUTION MSC.139(76)
(adopted on 5 December 2002)
MANDATORY SHIP REPORTING SYSTEMSMSC 76/23/Add.1
ANNEX 13
Page 5
I:\MSC\76\23-ADD.1.DOC
3.3 Geographical position for submitting reports
3.3.1 Eastbound traffic should make a report to TALLINN TRAFFIC when crossing the line
drawn from Bengtskär Lighthouse to 59 °33.30'N 022°30'E to 59°10'N 021 °30'E to K■pu
Peninsula or when entering the ship reporting area from south.
3.3.2 Westbound traffic should make a short report to HELSINKI TRAFFIC when crossing
longitude 026°30'E or when entering the ship reporting area from north.
3.3.3 A full report to the nearest shore station should be made on departure from port.
3.3.4 Further reports should be made to the relevant shore station whenever there is a change o
f
---CHUNK---
SOURCE: MSC.139(76).pdf
3.3.3 A full report to the nearest shore station should be made on departure from port.
3.3.4 Further reports should be made to the relevant shore station whenever there is a change o
f
navigational status or circumstance, particul arly in relation to items Q and R of the
reporting format.
3.4 Crossing traffic
3.4.1 Reports to the nearest shore station should be made on departure from a port within the
coverage area. Recognizing that ferries cr ossing between Helsinki and Tallinn generally
operate according to published schedules, speci al reporting arrangements can be made on
a ship-by-ship basis, subject to the approval of both HELSINKI TRAFFIC and
TALLINN TRAFFIC.
3.4.2 Further reports should be made to the relevant shore station whenever there is a change o

f
navigational status or circumstance, particul arly in relation to items Q and R of the report