on, as defined by IHO
standards.
11.3.7 It should also be possible to perform a complete route check to support the appraisal and planning process according to the applicable parts of resolution A.893(21). Detected objects should be available for review in graphical form and, on demand, in textual form.

SOURCE: MSC.530(106).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
objects should be available for review in graphical form and, on demand, in textual form.
11.3.8 It should be possible for the mariner to specify a cross track limit of deviation from the planned route at which an automatic off-track alarm should be activated.
11.4 Route monitoring
11.4.1 For route monitoring the selected route and own ship's position should appear whenever the display covers that area.
11.4.2 It should be possible to display a sea area that does not have the ship on the display (e.g. for look ahead, route planning), while route monitoring. If this is done on the display used for route monitoring, the automatic route monit oring functions (e.g. updating ship's position, and providing alerts and indications) should be continuous. It should be possible to return to the route monitoring display covering own ship's position immediately by single operator action.
11.4.3 It should be possible to select that ECDIS gives an alarm and related graphical
---
SOURCE: MSC.530(106).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
11.4.3 It should be possible to select that ECDIS gives an alarm and related graphical
indication if, within a specified time or distance set by the mariner, own ship will pass closer than a user-selected distance from the safety contour. There should be a permanent indication when the safety contour alarm is deselected.
11.4.4 ECDIS should give a warning or caution, or indication, as selected by the mariner, and related graphical indication if, within a specified time or distance set by the mariner, own ship will pass closer than a user -selected distance from the boundary of a user -selectable category of prohibited area or of a geographical area for which special conditions exist (see appendix 4). The user -selectable categories should be the same as user selec tions for the display of objects and be based on IHO standards. There should be a permanent indication when any user -selectable categories are deselected. Details of the deselection should be
---
SOURCE: MSC.530(106).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
when any user -selectable categories are deselected. Details of the deselection should be
available on demand.
11.4.5 An alarm should be given when the s pecified cross track limit for deviation from the selected route, if defined by the mariner when route planning, is exceeded.
RESOLUTION MSC.530(106) (adopted on 7 November 2022)
PERFORMANCE STANDARDS FOR ELECTRONIC CHART DISPLAY AND INFORMATION SYSTEMS (ECDIS)
MSC 106/19/Add.1
Annex 22, page 10
I:\MSC\106\MSC 106/19/Add.1.docx
11.4.6 ECDIS should give a warning or caution or indication as selected by the mariner and related graphical indication if, continuing on its present course and speed, over a specified time or distance set by the mariner, own ship will pass closer than a user -specified distance from a user-selectable category of danger (e.g. obstruction, wreck, rock) that is shallower than the mariner's safety contour or a user -selectable category of aid to navigation. The
---
SOURCE: MSC.530(106).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf
the mariner's safety contour or a user -selectable category of aid to navigation. The
user-selectable categories should be the same as user selections for the display