ention
shall apply the requirements of this Convention as may be necessary to ensure that no more favourable treatment is given to ships of non-Parties to this Convention,
NOTING ALSO resolution MEPC.105(49) by which the Committee adopted the Guidelines for inspection of anti-fouling systems on ship on 18 July 2003,
NOTING FURTHER that by resolution MEPC.105(49), the Committee resolved to keep the 2003 Guidelines under review in the light of experience gained,
HAVING CONSIDERED, at its sixty-second session, the draft 2011 Guidelines for inspection of anti-fouling systems on ships developed by the Sub-Committee on Flag State Implementation at its nineteenth session,
1. ADOPTS the 2011 Guidelines for inspection of anti- fouling systems on ships, as set out in the annex to this resolution;
---CHUNK---
SOURCE: MEPC.208(62).pdf
Implementation at its nineteenth session,
1. ADOPTS the 2011 Guidelines for inspection of anti- fouling systems on ships, as set out in the annex to this resolution;
2. INVITES Governments to apply the 2011 Guidelines when exercising port State control inspections;
3. RECOMMENDS that the 2011 Guidelines be adopted as amendments to resolution A.787(19) on Procedures for port State control, as amended;
4. AGREES to keep the 2011 Guidelines under review in the light of experience gained; and
5. REVOKES the Guidelines adopted by resolution MEPC.105(49).
RESOLUTION MEPC.208(62)
Adopted on 15 July 2011
2011 GUIDELINES FOR INSPECTION OF ANTI-FOULING SYSTEMS ON SHIPSMEPC 62/24/Add.1
Annex 27, page 2
I:\MEPC\62\24-Add-1.doc
ANNEX
2011 GUIDELINES FOR INSPECTION OF ANTI-FOULING SYSTEMS ON SHIPS
1 INTRODUCTION
1.1 The right of the port State to conduct inspections of anti-fouling systems on ships is in Article 11 of the AFS Convention. The guidelines for conducting these inspections are described below.
1.2 Ships of 400 gross tonnage and above engaged in international voyages (excluding
---CHUNK---
SOURCE: MEPC.208(62).pdf
in Article 11 of the AFS Convention. The guidelines for conducting these inspections are described below.
1.2 Ships of 400 gross tonnage and above engaged in international voyages (excluding fixed or floating platforms, FSUs and FPSOs) will be required to undergo an initial survey before the ship is put into service or before the International Anti-fouling System Certificate (IAFS) is issued for the first time; and a survey should be carried out when the anti-fouling systems are changed or replaced.
1.3 Ships of 24 metres in length or more but less than 400 gross tonnage engaged in international voyages (excluding fixed or floating platforms, FSUs and FPSOs) will have to carry a Declaration on Anti-fouling Systems signed by the owner or authorized agent. Such declaration shall be accompanied by appropriate documentation (such as a paint receipt or a contractor invoice) or contain appropriate endorsement.
2 INITIAL INSPECTION
2.1 Ships required to carry an IAFS Certificate or Declaration on Anti-Fouling Systems (Parties of the AFS Convention)
2.1.1 The PSCO should check the validity of the IAFS Certificate or Declaration on
---CHUNK---
SOURCE: MEPC.208(62).pdf
2 INITIAL INSPECTION
2.1 Ships required to carry an IAFS Certificate or Declaration on Anti-Fouling Systems (Parties of the AFS Convention)
2.1.1 The PSCO should check the validity of the IAFS Certificate or Declaration on Anti-Fouling Systems, and the attached Record of Anti-Fouling Systems, if appropriate.
2.1.2 The only practical way to apply paint to the ship's bottom (underwater part) is in a dry dock. This means that the date of application of paint on the IAFS Certificate should be checked by comparing the period of dry-docking with the date on the certificate.
2.1.3 If the paint has been applied during a scheduled dry-dock period, it has to be registered in the ship's logbook (in order to be legal). Furthermore, this sch