arrying such cargo are operating in polar waters. Reference is made in particular to the 2012 Guidelines for the implementation of MARPOL Annex V (resolution MEPC.219(63), as amended by resolution MEPC.239(65)) and the 2012 Guidelines for the development of garbage management plans (resolution MEPC.220(63)).

4 Additional guidance under other environmental conventions and guidelines

4.1 Until the International Convention for the Control and Management of Ships ' Ballast Water and Sediments enters into force, the ballast water management provisions of the ballast water exchange standard, set out in regulation D-1, or the ballast wat er performance standard, set out in regulation D -2 of the Convention should be considered as appropriate.

---CHUNK---

SOURCE: MEPC.264(68).pdf

ballast water exchange standard, set out in regulation D-1, or the ballast wat er performance standard, set out in regulation D -2 of the Convention should be considered as appropriate.

The provisions of the Guidelines for ballast water exchange in the Antarctic treaty area (resolution MEPC.163(56)) should be taken into consideration , along with other relevant guidelines developed by the Organization.

4.2 In selecting the ballast water management system, attention should be paid to limiting conditions specified in the appendix of the Type Approval Certificate and the temperature under which the system has been tested, in order to ensure its suitability and effectiveness in polar waters.

4.3 In order to minimize the risk of invasive aquatic species transfers via biofouling, measures should be considered to minimize the risk of more rapid degradation of anti-fouling coatings associated with polar ice operations. Reference is made in particular to the 2011 Guidelines for the control and management of ships ' biofouling to minimize the transfer of invasive aquatic species (resolution MEPC.207(62)).

RESOLUTION MEPC.264(68)

(adopted on 15 May 2015)

---CHUNK---

SOURCE: MEPC.264(68).pdf

2011 Guidelines for the control and management of ships ' biofouling to minimize the transfer of invasive aquatic species (resolution MEPC.207(62)).

RESOLUTION MEPC.264(68)

(adopted on 15 May 2015)

INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 45 -

Table: Example of matters related to anti-fouling systems taken into consideration by some ice-going ships

(this table is used by some operators of ice-going ships)

Hull	Sea chest
Year round operation in ice-covered polar waters	■ Abrasion resistant coating. ■ Compliant with the AFS Convention. Thickness of anti-fouling system to be decided by shipowner.
Intermittent operation in ice-covered polar waters	■ Abrasion resistant low friction ice coating. ■ In sides, above bilge keel, max thickness of anti-fouling system 75 µm, to protect hull between application of anti-fouling system and next anticipated voyage to ice-covered waters. In bottom area thickness to be decided by shipowner. Composition of anti-fouling system should also be decided by the shipowner. ■ Compliant with the AFS Convention. Thickness of anti-fouling system to be decided by shipowner.

---CHUNK---

SOURCE: MEPC.264(68).pdf

area thickness to be decided by shipowner. Composition of anti-fouling system should also be decided by the shipowner.
■ Compliant with the AFS Convention. Thickness of anti-fouling system to be

decided by shipowner.
Category B
and C ships
■ Compliant with the AFS Convention. Thickness of anti-fouling system to be decided by shipowner.
■ Compliant with the AFS Convention. Thickness of anti-fouling system to be decided by shipowner.
RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 46 -
APPENDIX I
Form of Certificate for Ships operating in Polar Waters
POLAR SHIP CERTIFICATE
This Certificate shall be supplemented by a Record o