;
.2 45 n(–0.2) g/kWh when n is 130 or more but less than 2,000 rpm; and
.3 9.8 g/kWh when n is 2,000 rpm or more.
25 Refer to the 2014 Guidelines on the approved method process (resolution MEPC.243(66)).
26 Refer to the 2014 Guidelines in respect of the information to be submitted by an Administra
tion to the
Organization covering the certification of an approved method as required under regulation 13.7
.1 of
MARPOL Annex VI (resolution MEPC.242(66)).
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
---CHUNK---
SOURCE: MEPC.403(83).pdf
MARPOL Annex VI (resolution MEPC.242(66)).
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1
Annex 11, page 29
I:\MEPC\MEPC 83-17-Add.1.docx
7.5 Certification of an approved method shall be in accordance with chapter 7 of the
revised NOx Technical Code 2008 and shall include verification:
.1 by the designer of the base marine diesel engine to which the approved
method applies that the calculated effect of the approved method will not
decrease engine rating by more than 1.0%, increase fuel consumption by
more than 2.0% as measured according to the appropriate test cycle set forth
in the revised NOx Technical Code 2008, or adversely affect engine durability
or reliability; and
.2 that the cost of the approved method is not excessive, which is determined
by a comparison of the amount of NO x reduced by the approved method to
achieve the standard set forth in paragraph 7.4 of this regulation and the cost
of purchasing and installing such approved method.27
Certification
---CHUNK---
SOURCE: MEPC.403(83).pdf
by a comparison of the amount of NO x reduced by the approved method to
achieve the standard set forth in paragraph 7.4 of this regulation and the cost
of purchasing and installing such approved method.27
Certification
8 The revised NOx Technical Code 2008 shall be applied in the certification, testing and
measurement procedures for the standards set forth in this regulation.
9 The procedures for determining NO x emissions set out in the revised NO x Technical
Code 2008 are intended to be representative of the normal operation of the engine. Defeat
devices and irrational emission control strategies undermine this intention and shall not be
allowed. This regulation shall not prevent the use of auxiliary control devices that are used t
o
protect the engine and/or its ancillary equipment against operating conditions that could resul
t
in damage or failure or that are used to facilitate the starting of the engine.
Regulation 14
Sulphur oxides (SOx) and particulate matter
General requirements
1 The sulphur content of fuel oil used or carried for use on board a ship shall not
exceed 0.50% m/m.
---CHUNK---
SOURCE: MEPC.403(83).pdf
Regulation 14
Sulphur oxides (SOx) and particulate matter
General requirements
1 The sulphur content of fuel oil used or carried for use on board a ship shall not
exceed 0.50% m/m.
2 The worldwide average sulphur content of residual fuel oil supplied for use on board
ships shall be monitored taking into account the guidelines developed by the Organization.28
Requirements within emission control areas
3 For the purpose of this regulation, an emission control area shall be any sea area,
including any port area, designated by the Organization in accordance with the criteria and
procedures set forth in appendix III. The emission control areas under this regulation are:
.1 the Baltic Sea area as defined in regulation 1.11.2 of Annex I of the present
Convention;
27 The cost of an approved method shall not exceed 375 Special Drawing Rights/metric tonne NOx
calculated
in accordance with the cost-effectiveness (Ce) formula below:
Refer to Definitions for the cost-effectiveness formula in regulat