uidelines set out in appendix 2
of the 2014 Guidelines on survey and certification of the Energy Efficiency Design Index (EEDI)
(resolution
MEPC.254(67), as amended by resolutions MEPC.261(68) and MEPC.309(73)); consolidated text:
MEPC.1/Circ.855/Rev.2, as may be further amended).
RESOLUTION MEPC.334(76) (adopted on 17 June 2021)
2021 GUIDELINES ON SURVEY AND CERTIFICATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP IND
EX (EEXI)MEPC 76/15/Add.2
Annex 8, page 6
I:\MEPC\76\MEPC 76-15-Add.2.docx
4.2.3 The SFC should be corrected to the value corresponding to the ISO standard reference
conditions using the standard lower calorific value of the fuel oil, referring to ISO 15550:200
2 and
ISO 3046-1:2002. For the confirmation of the SFC, a copy of the approved NOX Technical File and
---CHUNK---
SOURCE: MEPC.334(76).pdf
conditions using the standard lower calorific value of the fuel oil, referring to ISO 15550:200
2 and
ISO 3046-1:2002. For the confirmation of the SFC, a copy of the approved NOX Technical File and
documented summary of the correction calculations should be submitted to the verifier.
4.2.4 For ships equipped with dual-fuel engine(s) using LNG and fuel oil, the CF-factor for gas
(LNG) and the specific fuel consumption (SFC) of gas fuel should be used by applying the criter
ia
specified in paragraph 4.2.3 of the 2014 Guidelines on survey and certification of the E nergy
Efficiency Design Index (EEDI), as amended,3 as a basis for the guidance of the Administration.
4.2.5 Notwithstanding paragraphs 4.2.3 and 4.2.4, in cases where overridable Shaft / Engine
Power Limitation is installed, or in cases where engines do not have a test report included in
the NOX
Technical File, SFC should be calculated in accordance with paragraph 2.2.3 of the EEXI Calcula
tion
Guidelines. For this purpose, actual performance records of the engine may be used if satisfact
ory
and acceptable to the verifier.
---CHUNK---
SOURCE: MEPC.334(76).pdf
Technical File, SFC should be calculated in accordance with paragraph 2.2.3 of the EEXI Calcula
tion
Guidelines. For this purpose, actual performance records of the engine may be used if satisfact
ory
and acceptable to the verifier.
4.2.6 The verifier may request further information from the submitter, as specified in
paragraph 4.2.7 of the EEDI Survey and Certification Guidelines, in addition to that contained
in the
EEXI Technical File, as necessary, to examine the calculation process of the attained EEXI.
4.2.7 In cases where the sea trial report as specified in paragraph 4.2.2.9 is submitted, the
verifier should request further information from the submitter to confirm that:
.1 the sea trial was conducted in accordance with the conditions specified in
paragraphs 4.3.3, 4.3.4 and 4.3.7 of the EEDI Survey and Certification
Guidelines, as applicable;
.2 sea conditions were measured in accordance with ISO 15016:2002 or the
equivalent if satisfactory and acceptable to the verifier;
.3 ship speed was measured in accordance with ISO 15016:2002 or the
equivalent if satisfactory and acceptable to the verifier; and
---CHUNK---
SOURCE: MEPC.334(76).pdf
equivalent if satisfactory and acceptable to the verifier;
.3 ship speed was measured in accordance with ISO 15016:2002 or the
equivalent if satisfactory and acceptable to the verifier; and
.4 the measured ship speed was calibrated, if necessary, by taking into account
the effects of wind, tide, waves, shallow water and displacement in
accordance with ISO 15016:2002 or the equivalent which may be acceptable
provided that the concept of the method is transparent for the verifier and
publicly available/accessible.
4.2.8 The estimated speed- power curve obtained from the tank test and/or numerical
calculations and/or the sea trial results calibrated by the tank test should be reviewed on the
basis of the relevant documents in accordance with the EEDI Survey and Certification
Guidelines, the de