7.5 of the revised MARPOL Annex VI
(MEPC.1/Circ.678).
28 Refer to the 2020 Guidelines for monitoring the worldwide average sulphur content of fuel o
ils supplied
for use on board ships (resolution MEPC.326(75)).
RESOLUTION MEPC.403(83) (adopted on 11 April 2025)
AMENDMENTS TO THE 2022 GUIDELINES ON SURVEY AND CERTIFICATION
OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)
Cost of approved method• 10•
Ce =----------
Power (kW) • 0.768 • 6,000 (hours/y ear) · 5 (years) · 6NOx (g/kWh) MEPC 83/17/Add.1
Annex 11, page 30
I:\MEPC\MEPC 83-17-Add.1.docx
.2 the North Sea area as defined in regulation 1.14.6 of Annex V of the present
Convention;
.3 the North American Emission Control Area, which means the area described
by the coordinates provided in appendix VII;
.4 the United States Caribbean Sea Emission Control Area, which means the
area described by the coordinates provided in appendix VII;
.5 the Mediterranean Sea Emission Control Area, which means the area
described by the coordinates provided in appendix VII;
---CHUNK---
SOURCE: MEPC.403(83).pdf
area described by the coordinates provided in appendix VII;
.5 the Mediterranean Sea Emission Control Area, which means the area
described by the coordinates provided in appendix VII;
.6 the Canadian Arctic Emission Control Area, which means the area described
by the coordinates provided in appendix VII;
.7 the Norwegian Sea as defined in regulation 13.9.4 of Annex II of the present
Convention; and
.8 the North -East Atlantic Emission Control Area, which means the area
described by the coordinates provided in appendix VII.
4 While a ship is operating within an emission control area, the sulphur content of fuel
oil used on board that ship shall not exceed 0.10% m/m.
5 The sulphur content of fuel oil referred to in paragraph 1 and paragraph 4 of this
regulation shall be documented by its supplier as required by regulation 18 of this Annex.
6 Those ships using separate fuel oils to comply with paragraph 4 of this regulation and
entering or leaving an emission control area set forth in paragraph 3 of this regulation shall
carry a written procedure showing how the fuel oil changeover is to be done, allowing sufficien
t
---CHUNK---
SOURCE: MEPC.403(83).pdf
entering or leaving an emission control area set forth in paragraph 3 of this regulation shall
carry a written procedure showing how the fuel oil changeover is to be done, allowing sufficien
t
time for the fuel oil service system to be fully flushed of all fuel oils exceeding the applica
ble
sulphur content specified in paragraph 4 of this regulation prior to entry into an emission con
trol
area. The volume of low sulphur fuel oils in each tank as well as the date, time and position o
f
the ship when any fuel oil changeover operation is completed prior to the entry into an emissio
n
control area or commenced after exit from such an area shall be recorded in such logbook or
electronic record book29 as prescribed by the Administration.
7 During the first 12 months immediately following entry into force of an amendment
designating a specific emission control area under paragraph 3 of this regulation, ships
operating in that emission control area are exempt from the requirements in paragraphs 4 and
6 of this regulation and from the requirements of paragraph 5 of this regulation insofar as the
y
relate to paragraph 4 of this regulation.
---CHUNK---
SOURCE: MEPC.403(83).pdf
operating in that emission control area are exempt from the requirements in paragraphs 4 and
6 of this regulation and from the requirements of paragraph 5 of this regulation insofar as the
y
relate to paragraph 4 of this regulation.
In-use and onboard fuel oil sampling and testing
8 If the competent authority of a Party requires the in -use or onboard sample to be
analysed, it shall be done in accordance with the verification procedure set forth in appendix
VI
to determine whether the fue