ble Shaft / Engine Power Limitation is installed in accordance with
the 2021 Guidelines on the shaft / engine power limit to comply with the EEXI requirements
and use of a power reserve (resolution MEPC.335(76)), PME(i) is 83% of the limited installed
power (MCRlim) or 75% of the original installed power (MCR), whichever is lower, for each main
engine (i). In cases where the overridable Shaft / Engine Power Limitation and shaft
generator(s) are installed, in referring to paragraph 2.2.5.2 (option 1) of the EEDI Calculatio
n
Guidelines, "MCRME" should be read as "MCRlim".SOURCE: MEPC.333(76).pdf
engine (i). In cases where the overridable Shaft / Engine Power Limitation and shaft
generator(s) are installed, in referring to paragraph 2.2.5.2 (option 1) of the EEDI Calculatio
n
Guidelines, "MCRME" should be read as "MCRlim".
For LNG carriers having steam turbine or diesel electric propulsion, PME(i) is 83% of the limit
ed
installed power (MCRlim, MPPlim), divided by the electrical efficiency in case of diesel electr
ic
propulsion system, for each main engine (i). For LNG carriers, the power from combustion of
( )
mrefwl c i
nef
f
i
MEFMEieffieffAEFAE
nPTI
i
neff
i
iAEeffieffiPTI
n
j
jAEFAEAEiMEiFME
nME
i
iME
n
j
j
f V fCapacity f f f
SFC C P fSFC C P f P fSFC C PSFC C P f
. . . . . .
⎜⎟⎜⎟⎛ ∗ ∗– ⎜⎟⎜⎟⎛ ⎜⎟⎜⎟⎛ – · + ∗+ ⎜⎟⎜⎟⎛ ⎜⎟⎜⎟⎛ ΣΣ ΣΠΣΠ = · · ··= = ·=· ··= ·= 1) ( )
(1 1) () () (1) () (1) (1
RESOLUTION MEPC.333(76) (adopted on 17 June 2021)
2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP IN
DEX (EEXI)MEPC 76/15/Add.2
Annex 7, page 4
I:\MEPC\76\MEPC 76-15-Add.2.docx
the excessive natural boil-off gas in the engines or boilers to avoid releasing to the atmosphe
re
---CHUNK---
SOURCE: MEPC.333(76).pdf
Annex 7, page 4
I:\MEPC\76\MEPC 76-15-Add.2.docx
the excessive natural boil-off gas in the engines or boilers to avoid releasing to the atmosphe
re
or unnecessary thermal oxidation should be deducted from PME(i) with the approval of the
verifier.
2.2.2 PAE(i) ; Power of auxiliary engines
2.2.2.1 PAE(i) is calculated in accordance with paragraph 2.2.5.6 of the EEDI Calculation
Guidelines.
2.2.2.2 For ships where power of auxiliary engines (PAE) value calculated by
paragraphs 2.2.5.6.1 to 2.2.5.6.3 of the EEDI Calculation Guidelines is significantly diff eren
t
from the total power used at normal seagoing, e.g. in cases of passenger ships, the PAE value
should be estimated by the consumed electric power (excluding propulsion) in conditions when
the ship is engaged in a voyage at reference speed (Vref) as given in the electric power table
,
divided by the average efficiency of the generator(s) weighted by power (see appendix 2 of the
EEDI Calculation Guidelines).
2.2.2.3 In cases where the electric power table is not available, the P AE value may be
approximated either by:
.1 annual average figure of P AE at sea from onboard monitoring obtained prior
---CHUNK---
SOURCE: MEPC.333(76).pdf
EEDI Calculation Guidelines).
2.2.2.3 In cases where the electric power table is not available, the P AE value may be
approximated either by:

.1 annual average figure of P AE at sea from onboard monitoring obtained prior to the EEXI certification;
.2 for cruise passenger ships, approximated value of power of auxiliary engines (PAE,app), as defined below:
■■■■■■,■■■■■■ = 0.1193 × ■■■■ + 1814.4 [kW]
.3 for ro-ro passenger ships, approximated value of power of auxiliary engines (PAE,app), as defined below:
■■■■■■,■■■■■■ = 0.866 × ■■■■0.732 [kW]
2.2.3 Vref ; Ship speed
2.2.3.1 For ships falling into the scope of the EEDI requirement, the ship speed V ref should be obtained from an approved speed-power curve as defined in the 2014 Guidelines on survey and certification of the Energy Efficiency Design Index (EEDI) , as amended (resolution MEPC.254(67), as amended).
2.2.3.2 For ships not falling into the scope o