EPFS Navigation control data (7.5)
or Navigation status and data display
(7.7)
GPS Res. A.819(19), as amended,
MSC.112(73)
or GALILEO, Res. MSC.233(82)
or GLONAS, Res. MSC.53(66), as amended
MSC.113(73)
SDME Navigation control data (7.5)
or Navigation status and data display
(7.7)
Res. MSC.96(72)
3.6 The application of the alert management is specified in module C.
3.7 Other relevant standards
3.7.1 The workstation design, layout and arrangeme nt is not addressed in this performance standards, but in MSC/Circ.982.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 6
I:\MSC\83\28-Add-3.doc
4 Definitions
For the purpose of these standards the definitions in Appendix 1 apply.
Module A ■ Integration of Information
---CHUNK---
SOURCE: MSC.252(83).pdf
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 6
I:\MSC\83\28-Add-3.doc
4 Definitions
For the purpose of these standards the definitions in Appendix 1 apply.
Module A ■ Integration of Information
5 Requirements for integration of navigational information
5.1 Interfacing and data exchange
5.1.1 An INS should combine, process and evaluate data from connected sensors and sources.
5.1.2 The availability, validity and integrity of data exchange within the INS and from connected sensors and sources should be monitored.
5.1.3 A failure of data exchange should no t affect any independent functionality.
5.1.4 Interfacing to, from, and within the INS s hould comply with international standards for data exchange and interfacing as appropriate.
5.1.5 The interface(s) should comp ly with the interface requireme nts of the alert management as described in Module C of these performance standards.
5.2 Accuracy
5.2.1 INS data should comply with the accuracy and resolution required by applicable performance standards of the Organization.
5.3 Validity, plausibility, latency
5.3.1 Validity
---CHUNK---
SOURCE: MSC.252(83).pdf
5.2 Accuracy
5.2.1 INS data should comply with the accuracy and resolution required by applicable performance standards of the Organization.
5.3 Validity, plausibility, latency
5.3.1 Validity
5.3.1.1 Data failing validity checks should not be used by the INS for functions dependent on these data, unless for cases where the relevant performance standards specifically allow use of invalid data. There should be no side effects for functions not depending on this data.
5.3.1.2 When data used by the INS for a function becomes invali d, or unavailable, a warning should be given. When data not actually in use by the INS becomes invalid, or unavailable, a th is
should be indicated at least as a caution.
5.3.2 Plausibility
5.3.2.1 Received or derived data that is used or distributed by the INS should be checked for plausible magnitudes of values.
5.3.2.2 Data which has failed the plausibility checks should not be used by the INS and shou ld
not affect functions not dependent on these data.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
---CHUNK---
SOURCE: MSC.252(83).pdf
not affect functions not dependent on these data.

5.3.3 Latency
5.3.3.1 Data latency (timeliness and repetition rate of data) within the INS should not degr ade
the functionality specified in the relevant performance standards.
5.4 Consistent common refe rence system (CCRS)
5.4.1 Consistency of data
5.4.1.1 The INS should ensure that the different types of information ar e distributed to the relevant parts of the system, app