comprised by the INS or connected to the INS in identical
manner and should incorporate all alerts that are critical to the safety of navigation.
3 MSC.128(75), MSC.191(79).
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 24
I:\MSC\83\28-Add-3.doc
18.4 The logical architecture of the alert mana gement and the handling concept for alerts
---CHUNK---
SOURCE: MSC.252(83).pdf
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 24
I:\MSC\83\28-Add-3.doc
18.4 The logical architecture of the alert mana gement and the handling concept for alerts
should provide the capability to minimize the number of alerts especially those on a high prior
ity
level (e.g. using system knowledge from redundancy concepts inside INS and evaluating inherent
necessities for alerts against navigational situat ions, operational modes or activated navigat
ional
functions).
18.5 It should be possible to provide the centr al alert management HMI at least on the
navigating and manoeuvring workstation and allowing the handling by the bridge team.
18.6 The audible announcement of alerts should en hance the guidance of the bridge team to
the task stations or displays which are directly assigned to the function generating the alert
and
presenting the cause of the announcement and related information for decision support, e.g.,
dangerous target alarms should appear and have to be acknowledged at the workstation where the
collision avoidance function is provided.
---CHUNK---
SOURCE: MSC.252(83).pdf
presenting the cause of the announcement and related information for decision support, e.g.,
dangerous target alarms should appear and have to be acknowledged at the workstation where the
collision avoidance function is provided.
18.7 As alerts can be displayed at several locations , the system should be consistent as far
as
practicable with respect to how alerts are displayed, silen ced and acknowledged at any one tas
k
station of the INS.
19 Priorities and categories
19.1 Priorities of alerts
19.1.1 The alert management should distinguis h between the three priorities listed:
• Alarms
• Warnings and
• Cautions
19.1.2 Alarms should indicate conditions requiri ng immediate attention and action by the brid
ge
team.
19.1.3 Warnings should indicate changed conditions and should be presented for precautionary
reasons which are not immediately hazardous but which may become so, if no action is taken.
19.1.4 Cautions should indicate a condition wh ich does not warrant an alarm or warning
condition, but still requires attentio n and out of the ordinary consid eration of the situatio
n or of
given information.
---CHUNK---
SOURCE: MSC.252(83).pdf
19.1.4 Cautions should indicate a condition wh ich does not warrant an alarm or warning
condition, but still requires attentio n and out of the ordinary consid eration of the situatio
n or of
given information.
19.1.5 Alerts additional to the alerts required by the organization shoul d be assigned to an
priority level using the criteria for classification.
19.2 Criteria for classification of alerts
19.2.1 Criteria for classi fication of alarms:
• conditions requiring immediate attention and action by the br idge team to avoid any
kind of hazardous situation and to maintain the safe navigation of the ship
• or escalation required as alarm from a not acknowledged warning.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 25

19.2.2 Criteria for classification of warnings:
• Conditions or situations whic h require immediate attenti on for precautionary reasons,