02)
RECOMMENDATION FOR THE PROTECTION
OF THE AIS VHF DATA LINKRESOLUTION MSC.140(76)
(adopted on 5 December 2002)
RECOMMENDATION FOR THE PROTECTION
OF THE AIS VHF DATA LINK
---CHUNK---
SOURCE: MSC.141(76).pdf
RESOLUTION MSC.141(76)
(adopted on 5 December 2002)
REVISED MODEL TEST METHOD UNDER RESOLUTION 14
OF THE 1995 SOLAS CONFERENCEMSC 76/23/Add.1
I:\MSC\76\23-ADD.1.DOC
ANNEX 17
RESOLUTION MSC.141(76)
(adopted on 5 December 2002)
REVISED MODEL TEST METHOD UNDER RESOLUTION 14
OF THE 1995 SOLAS CONFERENCE
THE MARITIME SAFETY COMMITTEE,
RECALLING Article 38(c) of the Convention on the International Maritime Organization concerning the functions of the Committee,
RECALLING ALSO resolution 14 on Regi onal agreements on specific stability requirements for ro-ro passenger ships, adopted by the Conference of C ontracting Governments to the International Convention for the Sa fety of Life at S ea, 1974 (the 1995 SOLAS Conference),
NOTING that resolution 14 of the 1995 SOLA S Conference includes an option whereby the Administration may, as an alternative to calculation of the stability properties of a ship, accept model tests carried out for an individual ship in accordance with the model test method developed by the Organization, as appended to the Annex to the said resolution,
---CHUNK---
SOURCE: MSC.141(76).pdf
accept model tests carried out for an individual ship in accordance with the model test method developed by the Organization, as appended to the Annex to the said resolution,
BEING AWARE of the experience gained from model tests carried out in the past by Administrations using the aforementioned model test method,
BEARING IN MIND the compelling need to keep pace with new technology and knowledge,
HAVING CONSIDERED the recommendation made by the Sub-Committee on Stability and Load Lines and on Fishing Vessels Safety at its forty-fifth session,
1. ADOPTS the Revised Model Test Method under resolution 14 of the 1995 SOLAS Conference, including the associated Guidance Notes appended thereto, the text of which is set out in the Annex to the present resolution;
2. INVITES Member Governments which are party to regional agreements under resolution 14 of the 1995 SOLAS Conference to use the annexed Revised Model Test Method and associated Guidance Notes in lieu of the or iginal model test method appended to the said resolution.
RESOLUTION MSC.141(76)
(adopted on 5 December 2002)
REVISED MODEL TEST METHOD UNDER RESOLUTION 14
---CHUNK---
SOURCE: MSC.141(76).pdf
and associated Guidance Notes in lieu of the or iginal model test method appended to the said resolution.
RESOLUTION MSC.141(76)
(adopted on 5 December 2002)
REVISED MODEL TEST METHOD UNDER RESOLUTION 14
OF THE 1995 SOLAS CONFERENCEMSC 76/23/Add.1
ANNEX 17
Page 2
I:\MSC\76\23-ADD.1.DOC
ANNEX
REVISED MODEL TEST METHOD
1 Objectives
This revised model test method is a revision of the method contained in the Appendix to the Annex to resolution 14 of the 1995 SOLAS Conf erence. Since the entry into force of the Stockholm Agreement a number of model tests has been carried out in accordance with the test method previously in force. During these tests a number of refinements in the procedures have been identified. This new model test method aims to include these refinements and, together with the appended Guidance Notes, provide a more robust procedure for the assessment of survivability of a damaged ro-ro passenger ship in a seaway. In this respect, the model shoul
d
prove capable of withstanding the seaway define d in paragraph 4 below, in the worst damage case scenario.
2 Definitions
L BP is the length between perpendiculars
---CHUNK---
SOURCE: MSC.141(76).pdf

prove capable of withstanding the seaway define d in paragraph 4 below, in the worst damage case scenario.

2 Definitions

L BP is the length between perpendiculars

H S is the signifi