he practical experience gained through
the application of the Revised Interim Recommendations and submit relevant safety analysis
on ships carrying liquefied hydrogen in bulk.
6 REVOKES resolution MSC.420(97).

SOURCE: MSC.566(109).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResoluti
ons/MSC.566(109).pdf
on ships carrying liquefied hydrogen in bulk.
6 REVOKES resolution MSC.420(97).
RESOLUTION MSC.565(108) (adopted on 24 May 2024)
REVISED INTERIM RECOMMENDATIONS FOR CARRIAGE OF
LIQUEFIED HYDROGEN IN BULK
MSC 108/20/Add.1
Annex 20, page 2
I:\MSC\108\MSC 108-20-Add.1.docx
ANNEX
REVISED INTERIM RECOMMENDATIONS FOR CARRIAGE
OF LIQUEFIED HYDROGEN IN BULK
1 INTRODUCTION
1.1 For the carriage of liquefied gases in bulk by ships, the ships should comply with the
relevant requirements in the IGC Code, as amended ("the Code"). The scope of the Code
provided in paragraph 1.1.1 is:
"The Code applies to ships regardless of their size, including those of less
than 500 gross tonnage, engaged in the carriage of liquefied gases having a vapour
pressure exceeding 0.28 MPa absolute at a temperature of 37.8°C, and other
products, as shown in chapter 19, when carried in bulk".
1.2 A ship carrying liquefied hydrogen in bulk (hereinafter called "liquefied hydrogen
---
SOURCE: MSC.566(109).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResoluti
ons/MSC.566(109).pdf
products, as shown in chapter 19, when carried in bulk".
1.2 A ship carrying liquefied hydrogen in bulk (hereinafter called "liquefied hydrogen
carrier") should comply with the Code.
1.3 The Code requires that a gas carrier should comply with the minimum requirements
for the cargo listed in chapter 19. However, the requirements for liquefied hydrogen are not
specified in the Code.
1.4 This annex provides the Revised Interim Recommendations, as referred to in
paragraph 5 of the preamble of the Code, for the carriage of liquefied hydrogen in bulk, which
are intended to provide the basis for the future minimum requirements for the carriage of this
cargo. The Revised Interim Recommendations are intended to facilitate the establishme nt of
a tripartite agreement among the relevant Administrations for the carriage of liquefied hydroge
n
in bulk. However, they are not intended to prohibit the adoption of designs and arrangements
---
SOURCE: MSC.566(109).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResoluti
ons/MSC.566(109).pdf
in bulk. However, they are not intended to prohibit the adoption of designs and arrangements
other than those specified in the Code or in these Recommendations, at the discretion of the
Administrations.
1.5 These recommendations have been developed under the assumption that a liquefied
hydrogen carrier does not carry liquefied gases other than liquefied hydrogen. These
recommendations, therefore, are not applicable to liquefied hydrogen carriers carrying gase s
other than liquefied hydrogen.
1.6 In the Code, reference is made to paragraph 5 of the Preamble; paragraph 1.1.6.1;
and Note No.8 on completion of certificate in "model form of international certificate of fitne
ss
for the carriage of liquefied gases in bulk" in appendix 2 to the Code.
1.7 These Revised Interim Recommendations consist of the following parts. Part A is
applicable to ships with any type of cargo containment system. Part B and subsequent part(s)

SOURCE: MSC.566(109).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResoluti
ons/MSC.566(109).pdf
applicable to ships with any type of cargo containment system. Part B and subsequent part(s)
prescribe additional special requirements for cargo containment systems of specific types.
Part A: General (applicable to ships with any type of cargo containment
system);
Part B: Cargo containment systems of independent cargo tanks using vacuum