or after 1 January 1996 but before 1 January 2009, conforms
to performance standards not inferior to those specified in the annex to
resolution A.817(19), as amended by resolutions MSC.64(67) and
MSC.86(70);

SOURCE: MSC.530(106).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResoluti
ons/MSC.530(106).pdf
resolution A.817(19), as amended by resolutions MSC.64(67) and
MSC.86(70);
3 AGREES that, for the purpose of this resolution, the expression installed on or
after 1 January 2029 means:
(a) for ships for which the building contract is placed on or after 1 January 2029,
or in the absence of the contract, constructed on or after 1 January 2029, any
installation date on the ship; or
(b) for ships other than those prescribed in (a) above, a contractual delivery date
for the equipment or, in the absence of a contractual delivery date, the actual
delivery date of the equipment to the ship on or after 1 January 2029.
RESOLUTION MSC.530(106) (adopted on 7 November 2022)
PERFORMANCE STANDARDS FOR ELECTRONIC CHART DISPLAY AND
INFORMATION SYSTEMS (ECDIS)
MSC 106/19/Add.1
Annex 22, page 3
I:\MSC\106\MSC 106/19/Add.1.docx
ANNEX
PERFORMANCE STANDARDS FOR ELECTRONIC CHART DISPLAY AND
INFORMATION SYSTEMS (ECDIS)
1 SCOPE OF ECDIS

SOURCE: MSC.530(106).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResoluti
ons/MSC.530(106).pdf
I:\MSC\106\MSC 106/19/Add.1.docx
ANNEX
PERFORMANCE STANDARDS FOR ELECTRONIC CHART DISPLAY AND
INFORMATION SYSTEMS (ECDIS)
1 SCOPE OF ECDIS
1.1 The primary function of ECDIS is to contribute to safe navigation.
1.2 ECDIS with adequate backup arrangements may be accepted as complying with the
up-to-date charts and nautical publications required by regulations V/19 and V/27 of the 1974
SOLAS Convention. For the purpose of this document, the definition of electronic navigational
data service (ENDS) encompasses the nautical charts and nautical publications as defined in
SOLAS chapter V and IHO standards in force.
1.3 ECDIS should be capable of displaying all nautical information necessary for safe and
efficient navigat ion, originated and distributed by or on the authority of a government ,
authorized hydrographic office or other relevant government institution, as required by SOLAS
regulations V/19 and V/27.

SOURCE: MSC.530(106).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResoluti
ons/MSC.530(106).pdf
authorized hydrographic office or other relevant government institution, as required by SOLAS
regulations V/19 and V/27.
1.4 ECDIS should facilitate simple and reliable updating of the ENDS.
1.5 ECDIS should reduce the navigational workload compared to using the paper chart
and paper nautical publications. It should enable the mariner to execute in a convenient and
timely manner all route planning, route monitoring and positioning. It should be capable of
continuously indicating, monitoring and recording the ship's position.
1.6 The ECDIS display may also b e used for the display of radar, radar tracked target
information, AIS and other appropriate data layers to assist in route monitoring.
1.7 ECDIS should provide appropriate alerts or indications with respect to the information
displayed or malfunction of the equipment (see appendix 5). ECDIS should meet the
requirements of the Performance standards for bridge alert management (resolution
MSC.302(87)).

SOURCE: MSC.530(106).pdf
URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResoluti
ons/MSC.530(106).pdf
requirements of the Performance standards for bridge alert management (resolution
MSC.302(87)).
1.8 When the relevant chart information is not available in the appropriate form (see
section 4), some ECDIS equipment may operate in the raster chart display system (RCDS)
mode as defined in appendix 7. RCDS m