RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 RESOLlITION HEPC. S2 (32)
adopted on 6 March 1992
&~ENDHENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING
TO THE I~TERNATI ON AL CONVENTION FOR THE PREVENT ION OF
POLI.UTION FROM SHIPS, 1973
(New re gulations 13F and 13G a nd related amendments t o Annex I
o f MARPOL 73/78)
THE KARINE ENVIRONMENT PROTECTION COIiHITTEE,
RECALLING Article 38(a) of the Convention on th e International Maritim e Organization concerning the functions of the Committ ee,
NOTING art icle 16 of the Inter nat ion al Conventio n for the Prevention of Pollution from Ships, 1973 (hereinafter referred to as the "1973 Convention ") , and article VI of the Protocol of 1978 relating to the International Convention for th e Prevention of Pol l ution from Ships, 1973 (hereinafter referred t o as the " 1978 Protoc o l"), which confer upon the appropriate bod y of the Organization th e functi on of considering and adopting amendments to the 1973 Convention, as modifi ed by the 1978 Pr otocol (HARPOl 73/78),

referred t o as the " 1978 Protoc o l"), which confer upon the appropriate bod y of the Organization th e functi on of considering and adopting amendments to the 1973 Convention, as modifi ed by the 1978 Pr otocol (HARPOl 73/78),
NOTING ALSO resolution A. 675(16) on prevention of oi l pollution,
RECOGNIZING the sever ity of mar i ne pol lutio n i ncidents r es ul ting from tanke r casu alti es ,
DESIRING t o impr ove the r eq ui reme nts f or the de s ign and constru c tion of oil tan kers to pr event oi l pol lut ion i n t he event o f co lli sion or gr oundin g ,
HAVING CONSIDERED, at its thirty-second s ession, amendments to t he 1978 Pr ot ocol pr oposed and circulated in accor daoce with art ic le 1~ (2) (a) of the 1973 Convention,
1. ADOPTS, in accordance with arti cle 16(2)(d) of the 1973 Convention, amendments to t he Annex of the 1978 Prot oco l , the text of whi ch is set out in the Annex to the pre se nt res olution;
2. DETE~~ INE S , in accorda nce with article 16(2) (£)(iii) of t he 1973 Convention, that the amendments sha l l be deemed to have been acc epted on 6 Januarv 199 3, unless prior to thi s date one third or more of the Parties,

2. DETE~~ INE S , in accorda nce with article 16(2) (£)(iii) of t he
1973 Convention, that the amendments sha l l be deemed to have been acc epted
on 6 Januarv 199 3, unless prior to thi s date one third or more of the Parties,
or the Parties the combined merchant fleets of which constitute fifty per cent
or more of the gross tonnage o f the world ' s me r chant fleet , have communicated
to the Organization their objections t o the amendments;
3. INVITES the Parties to note that, in accordance with article 16(2) (g) (ii)
of the 1973 Conve ntio n, the amendments sh al l enter int o for ce on 6 J uly 1993
upon their acceptance in accordance with par agraph 2 above;
~. REQUESTS t he Secreta r y-Ge neral. in conf ormity with arti cle 16(2)(e) of
th e 1 973 Conve nti on, to trans mi t to a l l Partie s to HARPOL 73/78 certified
copies of the present resolution and the text of the amendment~ contained in
the Annex ~
5 . PURTRER REQUESTS th e Secretary-Gener al t o transmit copies of the
resolution and its Annex to the Members of th e Organization which are no t
PaY ties t o HARPOL 73/78;
RESOLUTION MEPC.52(32) adopted on 6 March 1992

the Annex ~
5 . PURTRER REQUESTS th e Secretary-Gener al t o transmit copies of the resolution and its Annex to the Members of th e Organization which are no t PaY ties t o HARPOL 73/78;
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 2 -
6. AGREES to develop as a matter of ur gency;
(a) guidelines for approval of alternative methods of design and construc t ion of oil tanke r s as called fo r in regulatio n 13F(S),
(b) guidelines for approval of alternative str uctural or operational arrangements as called for in regulation 13G(7) ; and
(e) guidelines for an enhanced progr amme of surveys and inspections as called for in regulation 13G(J).
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 3 -
ANNEX
AMENDMENTS TO ANNEX 1 OF KARPOL 73/78
Regulation 1
Definitions
The falloying new paragraph (8)(c) is inserted after the existing para ~r 8ph (B)(b):

FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 3 -
ANNEX
AMENDMENTS TO ANNEX 1 OF KARPOL 73/78
Regulation 1
Definitions
The falloying new paragraph (8)(c) is inserted after the existing
para ~r 8ph (B)(b):
"(c) Notwithstanding the provisions of subparagraph (a) of this
para~raph, conversion of an existing oil tanker co meet the
requirements of regu lat i on 13F or 13G of this Annex shal l not
be dee~ed to constitu t e a ma jor conversion for the purpose of
th is Annex."
Ne~ re gulations 13F and 13G
Th~ foll owi ng new regulations 13F and 13G are inserted after the
existing regulation 13£:
REGULATION 13F OF ANNEX I OF HARPOL 73/78
Prevention of oil pollution in the event of
collision or strandin g
(1) This re g1llatio n shall appl y t o oil tankers of 600 tons deadweight. and
above:
(a) for which th e bu ild ing contract is plac ed on or after
6 July 1993, or
(b) i n the absen ce of a building contract, the keels of ~hich are
laid or whi ch are at a simi lar stage of construction on or after
6 January 1994, or
(c) th e deliv ery of wh i ch is on or after 6 July 1996 , or
(d) whic h have und ergone a major conversion:

laid or whi ch are at a simi lar stage of construction on or after
6 January 1994, or
(c) th e deliv ery of wh i ch is on or after 6 July 1996 , or
(d) whic h have und ergone a major conversion:
(i) for whi ch the co ntract is placed after 6 July 1993; or
(ii) in the absence of a contract, the construction work of which
is begun after 6 January 1994; or
(iii) whi ch i s completed after 6 July 1996.
(2) Every oi l tanker of 5,000 t ons deadwe ight and above shall:
(a) in li eu of re ~ul ati on 13£, as applica b le, comply with the
req uir ements of paragraph (3) unless it is subject to the
prov isio ns of pa ra graphs (4) and (5); and
(b) comply, if applicable, with the requirem en ts of paragraph (6).
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION
FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 4 -
()) The ent ire cargo tank lengt h shall be protected by ballast ta nks or
spaces ot her th an c argo and fuel oil tan ks as £0 11 01.'5 :
(a) Win ~ ta nks or spaces
Win~ tank s or spaces shall exten d eit her for the full depth of the

()) The ent ire cargo tank lengt h shall be protected by ballast ta nks or spaces ot her th an c argo and fuel oil tan ks as £0 11 01.'5 :

(a) Win ~ ta nks or spaces

Win~ tank s or spaces shall exten d eit her for the full depth of the ship's side or from t he top of th e douhle bo tt om t o t he uppermos t deck, disre ga r ding a rounded gunwale where fitted. They shall be arranged such t hat th e cargo tanks are l oca ted inboard of th e moulded line of the side she ll plating, nOl.'here less than the dista nce w wh ich , as shown in figure 1, i s measured at an y cross-section at right angle s to the sid e shell, as specified be l o,",:

w = 0.5 ... DW (m) or

20,000

"" = 2 .0 m, whichever i s th e l es se r.

The minim um value of w = 1 . 0 m.

(b) Double bottom t anks or spac es

At any cross -sec tion the de pth of eac h double bo ttom tank or space shall be such that the distance h between t~e bottom of the cargo tanks an d the moul ded line of the bottom shell pl at ing measured at r ight an~les to the bottom shel l plating as shown in figure 1 i s not l ess t han specified be l ow :

h B/l5 (m) or

h 2.0 m, whichever is the lesser.

tanks an d the moul ded line of the bottom shell pl at ing measured at
r ight an~les to the bottom shel l plating as shown in figure 1 i s not
l ess t han specified be l ow :
h B/l5 (m) or
h 2.0 m, whichever is the lesser.
The minimum value of h = 1 . 0 m.
(c) Turn of the bilge ar ea or a t loca tion s without a clearly defined
t urn of the bi 1ge
Wh e n t he di st an ces h and wa re differen t , the dis ta nce w shall have
pr efere nce at levels exceed in g 1.5 h above t he base li ne as shown i n
figu re 1.
(d) The aggregate capaci t y of b a lla~t tanks
On crude oil tan kers of 20,000 t ons deadweight and ab ove and product
carriers of 30,000 tons deadwe ight and above, the aggregat e capac ity
of win g tanks, double bottom ta nks, f orepe ak tanks and afterpeak
tank s s ha l l n o t be less th an the capacity of segregated ballast
tan ks nece ssa ry t o meet the requir ements of regulation 13 . Wi ng
tanks or spaces and double bott om tank s used to meet the
requi re ments o f regulation 13 shall be located as un iformly as
pra cticable al ong the cargo tank length. Addi ti ona l segregated

tanks or spaces and double bott om tank s used to meet the
requi re ments o f regulation 13 shall be located as un iformly as
pra cticable al ong the cargo tank length. Addi ti ona l segregated
ballast capacity pr ovid ed for reducing l ongitudi na l hull girder
bending str ess, trim, e t c., may be located anywhere with in the sh i p .
(el Suction well s i n cargo tanks
Suc tion well s in cargo tanks may protrud e int o t he double botto m
below the bound a r y l ine defined by t he distance h provided tha t such
wells are as small as practica ble an d the distance between the well
bottom an d bot tom s hell pl a ti ng is not less than 0 . 5 h.
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 5 -
(f) Ballast and carg o piping
Ballast piping and other piping such as sounding and vent piping to
ballast tanks shall not pass through c argo tanks. Cargo piping and
similar piping to cargo tanks shall not pass through ballast tanks.
Exemptions to this requirement may be granted for short leng ths of

ballast tanks shall not pass through c argo tanks. Cargo piping and similar piping to cargo tanks shall not pass through ballast tanks. Exemptions to this requirement may be granted for short leng ths of piping, provided that they are completely welded or equivalent.

(4) (a) Double bottom tanks or spaces as required by paragraph O)(b) may be di s pensed with, provided that the design of the tanker is such that the cargo and vapour pressure exerted on the bottom shell plating forming a single boundary between the cargo and the sea does not exceed the external hydrostatic water pressure, as expressed by the following formu l a:

where~

P, height of cargo in contact with the bottom shell platin g i n metres

f maxi mum cargo density in t/m3

g m1nlMum operating draught under any expected loading condition in me tres

density of sea water in t/m3

maximum set pressure of pressure/vacuum valve provided for the cargo tank in bar s

safety factor 5 1.1

standard acceleration of gravity (9.81 111/92).

(b) Any horizontal partition necessary to fulfil the above requirements shal l be located at a height of not less than B/6 or 6 metres,

for the cargo tank in bar s
safety factor 5 1.1
standard acceleration of gravity (9.81 111/92).
(b) Any horizontal partition necessary to fulfil the above requirements shal l be located at a height of not less than B/6 or 6 metres, whichever is the lesser, but not more than 0.60, above the baseline where D is the moulded depth amidship s.
(c) The location of wing tanks or spaces shall be as defined in paragraph (l){a) except that, below a level 1.S h above t he baseline where h i s as defined in paragraph (3)(b), the cargo tank boundary line may be vertical down to the bottom plating, as shown in figure 2.
(5) Other methods of design and constructio n of oil tankers may als o be accepted as alternatives to the requirements prescribed in paragraph (3) , provided that such methods ensure at least the same level of protection against oil pollution in the event of collision or stranding an d are approved i n principl e by the Marine Environment Protection Committee based on gu i de line s developed by the Or ganization.
(6) For oi l tankers of 20,000 tons deadweight and above the damage assumptions prescribed in regulation 2S(2)(b) shall be supplemented by the

gu i de line s developed by the Or ganization.
(6) For oi l tankers of 20,000 tons deadweight and above the damage assumptions prescribed in regulation 2S(2)(b) shall be supplemented by the following assumed bottom raking damage:
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - , -
(8) lon g itudinal ex tent:
(i) ships of 75,000 tons deadweight and above :
0.6 L measured frorn t he forward perpen dicu l ar
(ii) ship s of less than 75 ,000 tons deadlo1eig hc
0.4 L measured from the forward perpendicular
(b) transverse extent: B/3 anywhere in the botto m
(e) verti cal extent: br each of th e ou ter hu ll .
(7) Oil tank ers of lea s than 5,000 tons deadweight shall:
(a) at least be fitted wi t h double bottom ta nks or spaces having such a depth that t he dis t a nce h s pecified in paragraph (3)(b) complies with the following:
h - B/15 (m) with a minim um value of h D 0.76 m;
in t he tu rn of the bi lge ar ea and at lo cat ion s wi tho ut a clearly def ined turn of the bilge, the cargo tank boundary line s hall run

with the following:
h - B/15 (m) with a minim um value of h D 0.76 m;
in t he tu rn of the bi lge ar ea and at lo cat ion s wi tho ut a clearly
def ined turn of the bilge, the cargo tank boundary line s hall run
parallel to the line of the mid-ship flat bottom as shown in
figure 3; and
(b) be pr ovided with cargo tanks so arranged that t he capacity of ea ch
cargo tank does not exceed 700 m3 unless win g tanks or space s are
arranged in accordance with paragraph (3)(a) comply ing with the
following:
w ~ 0.4 + 2.4 OW (m)
20,000
wit h a minimum valu e of w = 0 . 76 m.
(8) Oil shall not be car ried in any space exte nding forward of a co llision
bulkhead located in accordance with re gulation 11-1/11 of the Inte rnationa l
Conve nti on for the Safe t y of Li fe at Sea , 1974, as amended . An oi l tanker
th at i s not required t o have a col lisio n bulkh ead in acco rdan ce wi th that
re gula t ion shall not carry oi l in any space exten ding forwsrd of the
transverse plane perpen di cular to the centreline that is located as if it
were a collision bulkhead lo cated in accordance wi th that regulation.

re gula t ion shall not carry oi l in any space exten ding forwsrd of the transverse plane perpen di cular to the centreline that is located as if it were a collision bulkhead lo cated in accordance wi th that regulation.

(9) In appr ov in g the design and construc ti on of oil tanker s to be built in accordance with the provisions of this re gu lation , Admini s trations shall hav e due re gard t o the genersl s afet y aspe ct s including the ne ed f or the maintenance and ins pec t ions of wing and double bottom tank s or spaces.

RESOLUTION MEPC.52(32) adopted on 6 March 1992

AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 7

w w

h~w

h

Figure 1

Carg o tank boundary lines for the purpose of paragraph (3)

RESOLUTION MEPC.52(32) adopted on 6 March 1992

AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 8 -

w

1.5· h

base line

Figure 2

Cargo tank boundary 1 iues for th e purpose of paragraph (4)

RESOLUTION MEPC.52(32) adopted on 6 March 1992

FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 8 -
w
1.5· h
base line
Figure 2
Cargo tank boundary 1 iues for th e purpose of paragraph (4)
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION
FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 9 -
h

base line
Figure 3
Cargo tank boundary lines for the purpose of paragraph (7)
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION
FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 10 -
REGULATION 13C OF ANNEX I OF HARPOL 73 / 78
Prevention of oil pollution in the event of collision or stranding
Measures for existing tankers
(1) This regu l ation shall:
(a) apply to crude oil tankers of 20 ,000 t ons deadwei ght and above And
to product carrier s of 30,000 tons deadweight and Above, which ar e
contracted, the kee ls of which are laid. or which Are de l ivered
before the dates specified in regulation 13F(l) of this Annex; and
(b) not apply t o oil tankers comply ing with regulation 13F of this

contracted, the kee ls of which are laid. or which Are de l ivered
before the dates specified in regulation 13F(l) of this Annex; and
(b) not apply t o oil tankers comply ing with regulation 13F of this
Annex, whi ch are contracted, the keel s of whi c h are lai d, or are
de livered before the dates spe c ified in regulation 13F(I } of this
Annex; and
(e) not apply to oil tBn~ers covered by subparagraph (a) ab ove which
comply with regulation 13F(3)(a) and (b) or l3F(q) or 13F(5) of
this Annex, exce pt that the r equirement for minimum distances
between the cargo tank boundaries and th e ship side and bottom
plating need not be met in all re spects. In that event , the side
pr otection distances shall not be less than tho s e specified i n the
International Bulk Chemical Code for type 2 cargo tank location
a nd the bottom prote c tion shall compl y with re gu lation IJE(4)(b)
o f this Annex .
(2) The requirements of this regulation shall take effect as from
6 J uly 1995.
(3) (a) An oil tanker to which this regulati on applies shall be s uh je ct
to an enhanced programme of inspections during periodical,

o f this Annex .
(2) The requirements of this regulation shall take effect as from 6 J uly 1995.
(3) (a) An oil tanker to which this regulati on applies shall be s uh je ct to an enhanced programme of inspections during periodical, int ermediate and annual surveys, the scope and frequency of whi ch shal l at least compl y with the guidelines dev e l oped by t he Organization.
(b) An oil tank er over five years of age to which this regulation applies shall have on board, availabl e t o the competent authority of any Government of a State Party to t he present Convention, a compl ete file of the survey rep orts. in cludin g the results of all scantling measurement required , as well as t he statement of str uctural work carri ed out.
(c) Th is file shall be acco mpanied by a cond it ion evaluation report, containing conclusion s on th e structural condition of the ship and its residual scantlings, end orsed to indicate that it ha s been acc epted by or on behalf of the flag Administration. This file an d co ndit ion eval uati on report shall be prepared in a s tandar d format as con tain ed in the guide lines developed by the Organization.

acc epted by or on behalf of the flag Administration. This file
an d co ndit ion eval uati on report shall be prepared in a s tandar d
format as con tain ed in the guide lines developed by the Organization.
(4) An oil tanker not meeting the requirements of a new oil tank e r as
de fi ned in r egulation 1(2 6) of this Anne x shall comply with the requirement s
of regulation I J F of th i s Ann e~ not lat er than 25 yea rs after its date of
delivery, unle s s wing tanks or double bottom spa ces , not used for the carriage
of oil and meeting the widt h and height requirements of regulation 13E(q),
cover at lea st 30% of Lt for the fu ll dep th of th e ship on each side or at lea st 30% of the projected bott om shell area LPAs wi thin the length Lt . where L~ and the pro jected botto m shel l area EPAs are as de fined in reg ulat io n IJE(2), in whi ch case compl i ance with regulation l3F is required
not later than 30 year s after its date of delivery.
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION
FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 11 -

not later than 30 year s after its date of delivery.
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 11 -
(5) An oil tanker meet ing th e requirements of a new oil tanker as defined in r egu lation 1(26) o C this Annex shall comply with the requirements of re gul ation l3F of thi s Annex not later than 30 years after its date of deliv ery .
(6) Any new bal la st and load conditions resulting fr om the application of paragraph (~) of this regulation shal l be subject to approval of the Adminis tratio n which shall have regard, in parti cular, to longitudinal and lo ca l str ength, intact st abilit y and, if applicable, damage stability.
(7) Other s tructural or operational arrangements such as hydrostatically balanced loadin g may be accepte d as alternatives t o the requirements pre scri bed i n paragraph (4), provided that such alternatives ensure at least the same level of protection against oil pollution in the event of collision or s trandin g a nd are approved by the Administration based on guide l ines

pre scri bed i n paragraph (4), provided that such alternatives ensure at least
the same level of protection against oil pollution in the event of collision
or s trandin g a nd are approved by the Administration based on guide l ines
dev el oped by the Organi zation.
Regula tion 24(4)
Limitation of size and arrangement of car go tanks
The existing text of paragraph (4) is repla ced by the following:
"(4) The len gth o f each ca rgo tank shall not exceed 10 me t res or one of the
follow ing valu es, whichever is th e greater:
(a) Where no lon gitudi nal bulkhead is provided inside the ca r go tanks:
bi (0 .5 S- + 0.1) L
but not to exceed 0.2 L
(b) Where a centreline longitudinal bul khead is provided inside the
cargo tank s ~
(0 .25 bi + 0.15) L
B
(c) Where two or more longitudinal bulkheads are provided inside the
cargo tan ks;
(i) for wing cargo t anks;
0.2 L
(ii) for centre car go tanks:
(1) if bi i s eq ual to or greater than one fifth;
8
0.2 L
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION
FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 12 -

8
0.2 L
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 12 -
(2) if bi is le ss than One fifth:
B
Where no centreline lon gi t udinal bul khead is provided:
bi (0.5 +O.1)L
B
Where a centreline longitudinal bulkhead is provided;
(0.25 bi + 0.15) L
B
(d) "bi" is the minimum distance from the ship's side to the oute r lon gitudinal bulkhead of the tank in question measured inboard at right angles to the centrel in e a t t he lev el correspo nding t o the assigne d summer f reeboar d. "
AMENDMENTS TO THE RECORD OF CONSTRUCTION AND EQUIPMENT FOR OIL TANKERS (FORM B)
The following new paragraph 5.8 is inserted a fter the exi sti ng paragraph 5 .7;
" 5.8 Doubl e hull construction
5.8.1 The s hip is requir ed to be constru cte d according t o regulation 13F and complies with the requirements of :
5.8.2
5.8 . 3
5. 8 .4
5.8.5
.1
.2
. 3
paragra ph (3) (double hull co nstru ction)
paragraph (4) (mid-height deck tankers with double side const ru ctio n)
paragraph (5) (al te r native me t hod approved by

5.8.2
5.8 . 3
5. 8 .4
5.8.5
.1
.2
. 3
paragra ph (3) (double hull co nstru ction)
paragraph (4) (mid-height deck tankers with
double side const ru ctio n)
paragraph (5) (al te r native me t hod approved by
the Marin e Environment Protection Committee)
The ship is required to be co ns tructed according
to and complies wit h the require me nts o f
regulation l3F(7) (double bottom requirement s)
The ship is not r equi re d t o comply with the
requir ements of re gul atio n 13F
The ship is subject to re gulati on 13G and:
.1 is req uire d to comply wit h regulation 13F
not later thsn ..... .
. 2 is so arranged that the following tanks or
spaces are not us ed for th e carriage of oil
.... II
The ship is not sub j ec t to regulation l3G
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION
FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION

FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION
FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973