o which this chapter applies should be of a type
approved by the Administration. Such equipment should conform to
appropriate performance standards not inferior to those adopted by
the Organization*.
Refer to the following resolutions adopted by the Assembly of the
Organization:
.1 Resolution A.525(13): Performance standards for narrow-band
direct-printing telegraph equipment for the reception of
navigational and meteorological warnings and urgent information to
ships .
. 2 Resolution A.694(17): General requirements for shipborne radio
equipment forming part of the global maritime distress and safety
system (GMDSS) and for electronic navigational aids .
. 3 Resolution A.698(17): Performance standards for ship earth stations
capable of two-way communications and resolution A.570(14): Type
approval of ship earth stations .
. 4 Resoluti~n A.609(15): Performance standards for shipborne VHF radio
-
. 3 Resolution A.698(17): Performance standards for ship earth stations
capable of two-way communications and resolution A.570(14): Type
approval of ship earth stations .
. 4 Resoluti~n A.609(15): Performance standards for shipborne VHF radio
installations capable of voice communication and digital selective
calling .
. 5 Resolution A.610(15): Performance standards for shipborne MF radio
installations capable of voice communication and digital selective
calling .
. 6 Resolution A.613(15): Performance standards for shipborne MF/HF
radio installations capable of voice communication, narrow-band
direct-printing and digital selective calling .
. 7 Resolution A.695(17): Performance standards for float-free satellite
emergency position-indicating radio beacons (EPIRBs) operating on
406 MHz (see also Assembly resolution A.696(17): Type approval of
satellite emergency position-indicating radio beacons (EPIRBs)
operating in the COSPAS-SARSAT system).
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT (Footnote continued)
MSC 62/23/Add.2
ANNEX 18
Page 143

-
operating in the COSPAS-SARSAT system).
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT (Footnote continued)
MSC 62/23/Add.2
ANNEX 18
Page 143
.8 Resolution A.697(17): Performance standards for survival craft radar transponders for use in search and rescue operations •
. 9 Resolution A.612(15): Performance standards for float-free VHF emergency position-indicating radio beacons .
. 10 Resolution A.663(16): Performance standards for INMARSAT Standard-C ship earth stations capable of transmitting and rece~v~ng direct-printing communications and resolution A.570(14): Type approval of ship earth stations .
. 11 Resolution A.664(16): Performance standards for enhanced group call equipment .
. 12 Resolution A.661(16): Performance standards for float-free satellite emergency position-indicating radio beacons operating through the geostationary INMARSAT satellite system on 1.6 GHz •
. 13 Resolution A.662(16): Performance standards for float-free release and activation arrangements for emergency radio equipment .
. 14 Resolution A.699(17): System performance standard for the
-
. 13 Resolution A.662(16): Performance standards for float-free release and activation arrangements for emergency radio equipment .
. 14 Resolution A.699(17): System performance standard for the promulgation and co-ordination of maritime safety information using high-frequency narrow-band direct-printing .
. 15 Resolution A.700(17): Performance standards for narrow-band direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (MSI) by HF.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 144
14.14

14.14.1

14.14.2

14.14.3

14.14.4

14.14.5

14 .14.6

14.14.1

14.14.8

Maint e nance requ irements

Equipment should be so designed that the main units can be replaced readily without elaborate recalibration or readjustment.

Where applicable, equipment should be so constructed and installed that it is readily accessible for inspection and on-board maintenance purposes.

Adequate information should be provided to enable the equipment

-

Where applicable, equipment should be so constructed and installed that it is readily accessible for inspection and on-board maintenance purposes.

Adequate information should be provided to enable the equipment to be properl