of the heeling moments in 1.1.2 and 1.1.4
of that annex.
2.3.2 Multihull craft should meet the relevant requirements of annex 7 for all permitted cases of loading.
2.3.3 Subject to 2.3.4, all other craft should meet the following criteria in all permitted conditions of loading:
.1 resolution A.562(14) (weather criterion);
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 28
.2 the area under the righting lever curve (GZ curve) should not be less than 0.07 m.rad up to e = 15° when the maximum righting lever (GZ) occurs at e = 15° and 0.055 m.rad up to e = 30° when the maximum righting lever occurs at e = 30° or above. Where the maximum righting lever occurs at angles of between e = 15° and e = 30°, the corresponding area under the righting lever curve should be:
A = 0.055 + 0.001 (30° - emax) (m.rad)
where:
emax is the angle of heel in degrees at which the righting lever curve reaches its maximum;
.3 the area under the righting lever curve between e = 30° and e = 40° or between e = 30° and the angle of flooding
-
where:
emax is the angle of heel in degrees at which the righting lever curve reaches its maximum;
.3 the area under the righting lever curve between e = 30° and e = 40° or between e = 30° and the angle of flooding
ef *, if this angle is less than 40°, should not be less than 0.03 m.rad;
.4 the righting lever GZ should be at least 0.20 m at an angle of heel equal to or greater than 30°;
.5 the maximum righting lever should occur at an angle of heel not less than 15°; and
.6 the initial metacentric height GMo should not be less than 0.15 m.
2.3.4 Where the characteristics of the craft are unsuitable for application of 2.3.3, the Administration may accept alternative criteria equivalent to those stipulated in 2.3.3, appropriate to

the type of craft and area of operation.
2.4 Intact stability in the non - displacement mode
2.4.1 The requirements of this section and section 2.12 should be applied on the assumption that any stabilization systems fitted are fully operational.
2.4.2 Suitable calculations should be carried out and/or tests conducted to demonstrate that, when operating in the non-displacement and
-
on the assumption that any stabilization systems fitted are fully operational.
2.4.2 Suitable calculations should be carried out and/or tests conducted to demonstrate that, when operating in the non-displacement and
transient modes within approved operational limitations, the craft will, after a disturbance causing roll, pitch, heave or heel due to turning or any combination thereof, return to the original attitude.
2.4.3 The roll and pitch stability on the first and/or any other craft of a series should be qualitatively assessed during operational safety trials as required by chapter 18 and annex 8. The results of such trials may indicate the need to impose operational limitations.
In applying this criterion, small openings through which progressive flooding cannot take place need not be considered as open.
WII576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 29
2.4.4 Where craft are fitted with surface piercing structure or appendages, precautions should be taken against dangerous attitudes
-
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 29
2.4.4 Where craft are fitted with surface piercing structure or appendages, precautions should be taken against dangerous attitudes
or inclinations and loss of stability subsequent to a collision with a submerged or floating object.
2.4.5 In designs where periodic use of cushion deformation is employed as a means of assisting craft control, or periodic use of cushion air exhausting to atmosphere for purposes of craft manoeuvring, the effects upon cushion-borne stability should be determined, and the limitations on the use by virtue of craft speed or attitude should be established.

2.4.6 In the case of an air-cushion vehicle fitted with flexible skirts, it should be demonstrated that the skirts remain stable under operational conditions.

2.5 Intact stability in the transient mode

2.5.1 Under weather conditions up to the worst intended conditions, the time to pass from the displacement mode to the non-displacement mode and vice versa should be minimized unless it is demonstrated that no substantial reduction of stability occurs during this transition.

-

time to pass from the d