ey can be rapidly placed in any
one of the 1iferafts. Alternatively, one radar transponder
should be stowed in each survival craft.
* Refer to the Recommendation on performance standards for survival
craft portable two-way VHF radiotelephone apparatus, adopted by the
Organization by resolution A.605(15).
** Refer to the Recommendation on performance standards for survival craft
-
craft portable two-way VHF radiotelephone apparatus, adopted by the
Organization by resolution A.605(15).
** Refer to the Recommendation on performance standards for survival craft
radar transponders for use in search and rescue operations, adopted by
the Organization by resolution A.697(17).
WI1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 84
8.2.2
8.2.3
8.2.3.1
8.2.3.2
Craft should be provided with the following on-board communications
and alarm systems:
.1 an emergency means comprising either fixed or portable
equipment or both for two-way communications between emergency
control stations, muster and embarkation stations and
strategic positions on board; and
.2 a general emergency alarm system complying with the
requirements of regulation III/50 of the Convention to be used
for summoning passengers and crew to muster stations and to
initiate the actions included in the muster list. The system
should be supplemented by either a public address system or
other suitable means of communication. The systems should be
-
for summoning passengers and crew to muster stations and to
initiate the actions included in the muster list. The system
should be supplemented by either a public address system or
other suitable means of communication. The systems should be
operable from the operating compartment.
Signalling eguipment
All craft should be provided with a portable daylight signalling

lamp which is available for use in the operating compartment at all times and which is not dependent on the craft's main source of electrical power.

Craft should be provided with not less than 12 rocket parachute flares, complying with the requirements of regulation 111/35 of the Convention, stowed in or near the operating compartment.

8.3 Personal liLe - saying appliances

8.3.1 Where passengers or crew have access to exposed decks under normal operating conditions, at least one lifebuoy on each side of the c 'raft capable of quick release from the control compartment and from a position at or near where it is stowed, should be provided with a self-igniting light and a self-activating smoke signal. The positioning and securing arrangements of the self-activating smoke

-

a position at or near where it is stowed, should be provided with a self-igniting light and a self-activating smoke signal. The positioning and securing arrangements of the self-activating smoke signal should be such that it cannot be released or activated solely by the accelerations produced by collisions or groundings.

8.3.2 At least one lifebuoy should be provided adjacent to each normal exit from the craft and on each open deck to which passengers and crew have access, subject to a minimum of two being installed.

8.3.3 Lifebuoys fitted adjacent to each normal exit from the craft should be fitted with buoyant lines of at least 30 m in length.

8.3.4

8.3.5

Not less than half the total
with self-igniting lights.
self-igniting lights should
accordance with 8.3.3.
number of lifebuoys should be fitted
However, the lifebuoys provided with
not include those provided with lines in

A lifejacket complying with the requirements of regulation 111/32.1 or 111/32.2 of the Convention should be provided for every person on board the craft and, in addition:

.1 a number of lifejackets suitable for children equal to at

-

A lifejacket complying with the requirements of regulation 111/32.1 or 111/32.2 of the Convention should be provided for every person on board the craft and, in addition:

.1 a number of lifejackets suitable for children equal to at least 10% of the number of passengers on board should be provided or such greater number as may be required to provide a lifejacket for each child;

.2 every passenger craft should carry lifejackets for not less than 5% of the total number of persons on board. These lifejackets should be stowed in conspicuous places on deck or at muster stations:
.3 a sufficient