)

(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

FOR HIGH SPEED CRAFT (Footnote continued)

MSC 62/23/Add.2

ANNEX 18

Page 143

.8 Resolution A.697(17): Performance standards for survival craft radar transponders for use in search and rescue operations •

. 9 Resolution A.612(15): Performance standards for float-free VHF emergency position-indicating radio beacons .

. 10 Resolution A.663(16): Performance standards for INMARSAT Standard-C ship earth stations capable of transmitting and rece~v~ng direct-printing communications and resolution A.570(14): Type approval of ship earth stations .

. 11 Resolution A.664(16): Performance standards for enhanced group call equipment .

. 12 Resolution A.661(16): Performance standards for float-free satellite emergency position-indicating radio beacons operating through the geostationary INMARSAT satellite system on 1.6 GHz •

. 13 Resolution A.662(16): Performance standards for float-free release and activation arrangements for emergency radio equipment .

. 14 Resolution A.699(17): System performance standard for the

-

. 13 Resolution A.662(16): Performance standards for float-free release and activation arrangements for emergency radio equipment .

. 14 Resolution A.699(17): System performance standard for the promulgation and co-ordination of maritime safety information using high-frequency narrow-band direct-printing .

. 15 Resolution A.700(17): Performance standards for narrow-band direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (MSI) by HF.

W/1687n/pp/EWP

RESOLUTION MSC.36(63)

(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

FOR HIGH SPEED CRAFT MSC 62/23/Add.2

ANNEX 18

Page 144

14.14

14.14.1

14.14.2

14.14.3

14.14.4

14.14.5

14 .14.6

14.14.1

14.14.8

Maint e nance requ irements

Equipment should be so designed that the main units can be replaced readily without elaborate recalibration or readjustment.

Where applicable, equipment should be so constructed and installed that it is readily accessible for inspection and on-board maintenance purposes.

Adequate information should be provided to enable the equipment

-

Where applicable, equipment should be so constructed and installed that it is readily accessible for inspection and on-board maintenance purposes.

Adequate information should be provided to enable the equipment to be properly operated and maintained, taking into account the recommendations of the Organization*.

Adequate tools and spares should be provided to enable equipment to be maintained .

The Administration should ensure that radio equipment required by this chapter is maintained to provide the availability of the functional requirements specified in 14.4 and to meet the recommended performance standards of such equipment.

On crafts engaged on voyages in sea areas Al and A2, the availability should be ensured by using such methods as duplication of equipment, shore-based maintenance or at-sea electronic maintenance capability, or a combinat5 .on of these, as may be approved by the Administration.

On crafts engaged on voyages in sea areas A3 and A4, the availability should be ensured by using a combination of at least two methods such as duplication of equipment, shore-based maintenance or at-sea electronic maintenance capability, as may

-

On crafts engaged on voyages in sea areas A3 and A4, the availability should be ensured by using a combination of at least two methods such as duplication of equipment, shore-based maintenance or at-sea electronic maintenance capability, as may be approved by the Administration, taking into account the I'ecommendations of the Organization"""".

However, crafts operating solely between ports where adequate facilities for shore-based maintenance of the radio installations are available and provided no journey between two such ports exceeds six hours, then the Administration may exempt such crafts from the

requirement to use at least two maintenance methods. For such crafts at least one maintenance method should be used.

* Refer to the Recommendation on general requirements for shipborne radio equipment forming part of the global maritime distress and safety system and for electronic navigational aids , adopted by the Organization by resolution A.694(11).

** Administrations should take account of the Recommendations on radio maintenance guidelines for the Global Maritime Distress and Safety System

-

and for electronic navigational aids , adopted by the Organization by resolution A.694