cating~;
.7 of transmitting and receiving** marine safety information;
.8 of transmitting and receiving general radiocommunications to and from shore-based radio systems or networks subject to 14.14.8; and
.9 of transmitting and receiving bridge-to-bridge communications.
* Refer to resolution A.614(15) on carriage of radar operating in the frequency band 9,300-9,500 MHz adopted by the Organization.
** It should be noted that craft may have a need for reception of certain maritime safety information while in port.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
-
frequency band 9,300-9,500 MHz adopted by the Organization.
** It should be noted that craft may have a need for reception of certain maritime safety information while in port.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 14.5
14.5.1
14.5.2
14.5.3
14.6
14.6.1
Radio installations
MSC 62/23/Add.2
ANNEX 18
Page 133
Every craft should be provided with radio installations capable of complying with the functional requirements prescribed by 14.4 throughout its intended voyage and, unless exempted under 14.3, complying with the requirements of 14.6 and, as appropriate for the sea area or areas through which it will pass during its intended voyage, the requirements of either 14.7, 14.8, 14.9 or 14.10.
Every radio installation should:
.1 be so located that no harmful interference of mechanical, electrical or other origin affects its proper use, and so as to ensure electromagnetic compatibility and avoidance of harmful interaction with other equipment and systems;
.2 be so located as to ensure the greatest possible degree of safety and operational availability;

-
as to ensure electromagnetic compatibility and avoidance of harmful interaction with other equipment and systems;
.2 be so located as to ensure the greatest possible degree of safety and operational availability;
.3 be protected against harmful effects of water, extremes of temperature and other adverse environmental conditions;
.4 be provided with reliable, permanently arranged electrical lighting, independent of the main sources of electrical power, for the adequate illumination of the radio controls for operating the radio installation; and
.5 be clearly marked with the call sign, the ship station identity and other codes as applicable for the use of the radio installation.
Coritrol of the VHF radiotelephone channels, required for navigational safety, should be immediately available on the navigating bridge convenient to the conning position, and where necessary, facilities should be available to permit radiocommunications from the wings of the navigating bridge.
Portable VHF equipment may be used to meet the latter provision.
Radio eguipment: General
Every craft should be provided with:
.1 a VHF radio installation capable of transmitting and receiving:
-
Portable VHF equipment may be used to meet the latter provision.
Radio eguipment: General
Every craft should be provided with:
.1 a VHF radio installation capable of transmitting and receiving:
.1.1 DSC on the frequency 156.525 MHz (channel 70). It should be possible to initiate the transmission of distress alerts on channel 70 from the position from which the craft is normally navigated*; and
.1.2 radiotelephony on the frequencies 156.300 MHz (channel 6), 156.650 MHz (channel 13) and 156.800 MHz (channel 16);
.2 a radio installation capable of maintaining a continuous DSC watch on VHF channel 70 which may be separate from, or combined with, that required by 14.6.1.1.1;~
Certain craft may be exempted from this requirement (see 14.8.4, 14.9.4, and 14.10.2.).
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18

.3 a radar transponder capable of operating in the 9 GHz band,
which:
.3.1
.3.2
should be so stowed that it can be easily utilized; and
may be one of those required by 8.2.1.2 for a survival
craft;
-

.3 a radar transponder capable of operating in the 9 GHz band,
which:
.3.1
.3.2
should be so stowed that it can be easily utilized; and
may be one of those required by 8.2.1.2 for a survival
craft;
.4 a receiver capable of receiving International NAVTEX service
broadcasts if the craft is engaged on voyages in any area in
which an International NAVTEX service is provided;
.5 a radio facility for reception of maritime safety information
by the INMARSAT enhanced group calling system* if the craft is
engaged