solution A.421(XI) concerning operational standards for
radiotelephone alarm signal generators, adopted by the Organization.
** This requirement can be met by INMARSAT ship earth stations capable of
two-way communications, such as Standard-A and B (resolution A.698(17»
or Standard-C (resolution A.663(16» ship earth stations. Unless
otherwise specified, this footnote applies to all requirements for an
INMARSAT ship earth station prescribed by this chapter.
W/16B7n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX lB
Page 136
14.7.2
14.7.3
14. B
l4.B.l
.5.2 ,the satellite EPIRB, required by 14.6.1.6, either by
installing the satellite EPIRB close to, or by remote
activation from, the position from which the craft is normally
navigated.
-
ANNEX lB
Page 136
14.7.2
14.7.3
14. B
l4.B.l
.5.2 ,the satellite EPIRB, required by 14.6.1.6, either by
installing the satellite EPIRB close to, or by remote
activation from, the position from which the craft is normally
navigated.
The VHF radio installation, required by 14.6.1.1, should also be
capable of transmitting and receiving general radiocommunications
using radiotelephony.
Craft engaged on voyages exclusively in sea area Al may carry, in
lieu of the satellite EPIRB required by 14.6.1.6, an EPIRB which
should be:
.1 capable of transmitting a distress alert using DSC on VHF
channel 70 and providing for locating by means of a radar
transponder operating in the 9 GHz band;
.2 installed in an easily accessible position;
.3 ready to be manually released and capable of being carried by

one person into a survival craft;
.4 capable of floating free if the craft sinks and of being
automatically activated when afloat; and
.5 capable of being activated manually.
Radio egui!?ment - Sea areas Al and A2
In addition to meeting the requirements of 14.6, every craft engaged
on voyages beyond sea area AI, but remaining within sea area A2,
-
.5 capable of being activated manually.
Radio egui!?ment - Sea areas Al and A2
In addition to meeting the requirements of 14.6, every craft engaged
on voyages beyond sea area AI, but remaining within sea area A2,
should be provided with:
.1 an MF radio installation capable of transmitting and
receiving, for distress and safety purposes, on the
frequencies:
.1.1 2,187.5 kHz using DSC; and
.1.2 2,182 kHz using radiotelephony;
.2 a radio installation capable of maintaining a continuous DSC
watch on the frequency 2,187.5 kHz which may be separate from,
or combined with, that required by 14.8.1.1.1; and
.3 means of initiating the transmission of ship-to-shore distress
alerts by a radio service other than MF operating either:
.3.1 through the polar orbiting satellite service on 406 MHz;
this requirement may be fulfilled by the satellite
EPIRB, required by 14.6.1.6, either by installing the
satellite EPIRB close to, or by remote activation from,
the position from which the craft is normally navigated;
or
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.8.2
14.8.3
14.8.4
14.9
-
the position from which the craft is normally navigated;
or
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.8.2

14.8.3
14.8.4
14.9
14.9.1
.3.2
.3.3
.3.3.1
.3.3.2
on HF using DSC; or

through the INMARSAT geostationary satellite service;
this requirement may be fulfilled by:
the equipment specified in 14.8.3.2; or
the satellite EPIRB, required by 14.6.1.6, either
by installing the satellite EPIRB close to, or by remote
activation from, the position from which the craft is
normally navigated.
It should be possible to initiate transmission of distress alerts by
the radio installations specified in 14.8.1.1 and 14.8.1.3 from the
position from which the craft is normally navigated.
The craft should, in addition, be capable of transmitting and
receiving general radiocommunications using radiotelephony or
direct-printing telegraphy by either:
.1 a radio installation operating on working frequencies in the
bands between 1,605 kHz and 4,000 kHz or between 4,000 kHz and
27,500 kHz. This requirement may be fulfilled by the addition
-
direct-printing telegraphy by either:
.1 a radio installation operating on working frequencies in the
bands between 1,605 kHz and 4,000 kHz or between 4,000 kHz and
27,500 kHz. This requirement may be fulfilled by the addition
of th