ply with the functional requirements of 14.4; and

.2 the Administration has taken into account the effect such exemptions may have upon the general efficiency of the service for the safety of all ships and craft.

* Refer to the NAVTEX manual approved by the Organization.

** Refer to resolution A.704(17) concerning provision of radio services for the Global Maritime Distress and Safety System (GMDSS), adopted by the Organization.

RESOLUTION MSC.36(63)

(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

FOR HIGH SPEED CRAFT MSC 62/23/Add.2

ANNEX 18

Page 132

14.3.2

14.3.3

14.4

14.4.1

-

Organization.

RESOLUTION MSC.36(63)

(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

FOR HIGH SPEED CRAFT MSC 62/23/Add.2

ANNEX 18

Page 132

14.3.2

14.3.3

14.4

14.4.1

An exemption may be granted under 14.3.1 only:

.1 if the conditions affecting safety are such as to render the full application of 14.6 to 14 . 10 unreasonable or unnecessary;

.2 in exceptional circumstances, for a single voyage outside the sea area or sea areas for which the craft is equipped; or

.3 prior to 1 February 1999, when the craft will be taken permanently out of service within two years of a date prescribed by 14.1 for the application of requirements of this chapter.

Each Administration should submit to the Organization, as soon as possible after the first of January in each year, a report showing all exemptions granted under 14.3.1 and 14.3.2 during the previous calendar year and giving the reasons for granting such exemptions.

Functional requirements

Every craft, while at sea, should be capable:
.1 except as provided in 14.7.1.1 and 14.9.1.4.3, of transmitting ship-to-shore distress alerts by at least two separate and
-
Functional requirements
Every craft, while at sea, should be capable:
.1 except as provided in 14.7.1.1 and 14.9.1.4.3, of transmitting ship-to-shore distress alerts by at least two separate and
independent means, each using a different radiocommunication service;
.2 of receiving shore-to-ship distress alerts;
.3 of transmitting and receiving ship-to-ship distress alerts;
.4 of transmitting and receiving search and rescue co-ordinating communications;
.5 of transmitting and receiving on-scene communications;
.6 of transmitting and, as required by 13.5, receiving signals for locating~;
.7 of transmitting and receiving** marine safety information;
.8 of transmitting and receiving general radiocommunications to and from shore-based radio systems or networks subject to 14.14.8; and
.9 of transmitting and receiving bridge-to-bridge communications.
* Refer to resolution A.614(15) on carriage of radar operating in the frequency band 9,300-9,500 MHz adopted by the Organization.
** It should be noted that craft may have a need for reception of certain maritime safety information while in port.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
-
frequency band 9,300-9,500 MHz adopted by the Organization.
** It should be noted that craft may have a need for reception of certain maritime safety information while in port.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 14.5
14.5.1
14.5.2
14.5.3
14.6
14.6.1
Radio installations
MSC 62/23/Add.2

Every craft should be provided with radio installations capable of complying with the functional requirements prescribed by 14.4 throughout its intended voyage and, unless exempted under 14.3, complying with the requirements of 14.6 and, as appropriate for the sea area or areas through which it will pass during its intended voyage, the requirements of either 14.7, 14.8, 14.9 or 14.10.

Every radio installation should:

.1 be so located that no harmful interference of mechanical, electrical or other origin affects its proper use, and so as to ensure electromagnetic compatibility and avoidance of harmful interaction with other equipment and systems;

.2 be so located as to ensure the greatest possible degree of safety and operational availability;

-

as to ensure electromagnetic compatibility and avoidance of harmful interaction with other equipment and systems;

.2 be so located as to ensure the greatest possible degree of safety and operational availability;

.3 be protected against harmful effects of water, extremes of temperature and other adverse environmental conditions;

.4 be provided with reliable, permanently arranged electrical lighting, independent of the main sources of electrical power, for the adequate illumination of the