gated■ should be applied as meaning ■from a position or positions which are

continuously manned and which are controlling the MODU while stationary at the site including

its drilling operations (i.e. normally the control room)■.

5 Refer to the World-Wide Navigational Warning Service (resolution A.706(17), as amended).

RESOLUTION MSC.506(105) (adopted on 28 April 2022)

OF MOBILE OFFSHORE DRILLING UNITS, 2009 (2009 MODU CODE)

MSC 105/20/Add.1

I:\MSC\105\MSC 105-20-Add.1.docx

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf

OF MOBILE OFFSHORE DRILLING UNITS, 2009 (2009 MODU CODE)

MSC 105/20/Add.1

I:\MSC\105\MSC 105-20-Add.1.docx

11.6 Radio life-saving appliances

Two-way VHF radiotelephone apparatus

11.6.1 All lifeboats should carry a two-way VHF radiotelephone apparatus.

11.6.2 At least two two -way VHF radiotelephone apparatuses should be available on the MODU, so stowed that they can be rapidly placed in any liferaft. 6 All two -way VHF radiotelephone apparatuses should conform to performance standards not inferior to those adopted by the Organization.

_____

6 The two -way VHF radiotelephone apparatus required by 11.6.2 may fulfil or partially fulfil the

requirements of SOLAS regulations IV/7.2, 7.3 or 7.4, as applicable.

Search and rescue locating device

11.6.3 All lifeboats should carry one radar SART or AIS-SART.

11.6.4 At least two radar SARTs or AIS-SARTs should be available on the MODU, so stowed

---

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf

11.6.4 At least two radar SARTs or AIS-SARTs should be available on the MODU, so stowed

that they can be rapidly placed in any liferaft. 7 All SARTs or AIS -SARTs should conform to

performance standards not inferior to those adopted by the Organization.

_____

7 The radar SARTs or AIS-SARTs required by 11.6.4 may fulfil the requirements of SOLAS

regulations IV/7.1.3, 7.2, 7.3 or 7. 5, as applicable.

11.7 Helicopter communications

In order to ensure communication with helicopters, MODUs should carry an aeromobile VHF radiotelephone station complying with the relevant requirements of ICAO 8 and suitable for communication with helicopters in its area of operation.

_____

8 Refer to Volume 3, Part II of annex 10, and Part III, section II of annex 6 to the ICAO

Convention.

11.8 Internal communications

All types of MODUs should be fitted with efficient means of communication between the control

---

URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf

11.8 Internal communications

All types of MODUs should be fitted with efficient means of communication between the control

room, the bridge (if provided) and position or positions fitted with facilities for operation of radio

equipment.

11.9 Performance standards

All radio equipment should be of a type approved by the Administration issuing the licence.

Such equipment should conform to appropriate performance standards not inferior to those

adopted by the Organization.9

_____

9 Refer to the following performance standards adopted by the Organization:

General requirements

.1 General requirements for shipborne radio equipment forming part of the Global Maritime

Distress and Safety System (GMDSS) and for electronic navigational aids (resolution

A.694(17));

.2 Performance standards for the presentation of navigation-related information on shipborne

navigational displays (resolution MSC.191(79), as amended);

URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.506(105).pdf

navigational displays (resolution MSC.191(79), as amended);

.3 Performance standards for bridge alert management (resolution MSC.302(87));

RESOLUTION MSC.506(105) (adopted on 28 April 2022)

OF MOBILE OFFSHORE DRILLING UNITS, 2009 (2009 MODU CODE)

MSC 105/20/Add.1

I:\MSC\105\MSC 105-20-Add.1.docx

VHF equipment

.4 Performance standards for shipborne VHF radio installations capable of voice

communication and digital selective calling (resolution MSC.511(105));

.5 Performance standards for survival craft portable two-way VHF radiotelephone apparatus

(resolution MSC.515(105));

.6 Recommendation on Performance standards for on -scene (aeronautical) portable

two-way VHF radiotelephone appar