ship■s structure referred to in SOLAS regulation II-1/3-6 on Access to and

within spaces in the cargo area of oil tankers and bulk carriers.

Definitions

Terms used in the Technical provisions have the same meaning as those defined in the 1974

SOLAS Convention, as amended, and in resolution A.744(18), as amended.

Technical provisions

1 Structural members subject to the close-up inspections and thickness measurements of the

ship■s structure referred to in SOLAS regula tion II-1/3-6, except those in double bottom spaces,

shall be provided with a permanent means of acce ss to the extent as specified in table 1 and

table 2, as applicable. For oil tankers and wing ba llast tanks of ore carriers, rafting may be used

in addition to the specified permanent means of access, provided that the structure allows for its

safe and effective use.

2 Elevated passageways, where fitted, sha ll have a minimum width of 600 mm and be

provided with toe boards not less than 150 mm high and guard rails over both sides of their entire

-

safe and effective use.

2 Elevated passageways, where fitted, sha ll have a minimum width of 600 mm and be

provided with toe boards not less than 150 mm high and guard rails over both sides of their entire

length. Sloping structure providing part of the access shall be of a non-skid construction. Guard

rails shall be 1,000 mm in height and consist of a rail and intermediate bar 500 mm in height and

of substantial construction. Stanchions shall be not more than 3 m apart.

3 Access to elevated passageways and vertical openings from the ship■s bottom shall be

provided by means of easily accessible passageways, la dders or treads. Treads shall be provided

with lateral support for the foot. Where the rungs of ladders are fitted against a vertical surface,

the distance from the centre of the rungs to the surface shall be at least 150 mm. Where vertical

manholes are fitted higher than 600 mm above the walking level, access shall be facilitated by

means of treads and hand grips with platform landings on both sides.

RESOLUTION MSC.133(76)

(adopted on 12 December 2002)

ADOPTION OF TECHNICAL PROVISIONS FOR MEANS OF

ACCESS FOR INSPECTIONSMSC 76/23/Add.1

ANNEX 2

-

means of treads and hand grips with platform landings on both sides.

RESOLUTION MSC.133(76)

4 Tunnels passing through cargo holds shall be e quipped with ladders or steps at each end of the hold so that personnel may easily cross such tunnels.

5 Permanent ladders, except for vertical ladders, which are fitted on vertical structures for close-up inspection or thickness measurement, shall be inclined at an angle of less than 70".

There shall be no obstructions within 750 mm of th e face of the inclined ladder, except that in way of an opening this clearance may be reduced to 600 mm. The flights of ladders shall not be more than 9 m in actual length. Resting platform s of adequate dimensions shall be provided.

Ladders and handrails shall be constructed of steel or equivalent material of adequate strength and stiffness and securely attached to the ta nk structure by stays. The method of support and length of stay shall be such that vibration is reduced to a practical minimum. In cargo holds,

-

and stiffness and securely attached to the ta nk structure by stays. The method of support and length of stay shall be such that vibration is reduced to a practical minimum. In cargo holds,

ladders shall be designed and arranged so that th e risk of damage from cargo handling gear is minimized.

6 The width of ladders between stringers shall not be less than 400 mm. The treads shall be equally spaced at a distance apart, measured vertically, of between 250 mm and 300 mm. When steel is used, the treads shall be formed of tw o square bars of not less that 22 mm by 22 mm in section, fitted to form a horizontal step with the edges pointing upward. The treads shall be carried through the side stringers and attached thereto by double continuous welding. All sloping ladders shall be provided with handrails of s ubstantial construction on both sides, fitted at a convenient distance above the treads.

7 No free-standing portable ladder shall be more than 5 m long.

8 Portable ladders more than 5 m long may only be utilized if f itted with a remotely controlled mechanical device to secure the upper end of the ladder.

-

7 No free-standing portable ladder shall be more than 5 m long.

8 Po