e 2011 Guidelines for inspection of anti- fouling systems on ships, as set
out in the annex to this resolution;
2. INVITES Governments to apply the 2011 Guidelines when exercising port State
control inspections;
3. RECOMMENDS that the 2011 Guidelines be adopted as
A.787(19) on Procedures for port State control, as amended;
4. AGREES to keep the 2011 Guidelines under review in the light of experience
gained; and
5. REVOKES the Guidelines adopted by resolution MEPC.105(49).
RESOLUTION MEPC.208(62)
Adopted on 15 July 2011
2011 GUIDELINES FOR INSPECTION OF ANTI-FOULING SYSTEMS ON SHIPSMEPC 62/24/Add.1
Annex 27, page 2
I:\MEPC\62\24-Add-1.doc
ANNEX
2011 GUIDELINES FOR INSPECTION OF ANTI-FOULING SYSTEMS ON SHIPS
1 INTRODUCTION
1.1 The right of the port State to conduct inspections of anti-fouling systems on ships is
in Article 11 of the AFS Convention. The guidelines for conducting these inspections are
described below.
1.2 Ships of 400 gross tonnage and above engaged in international voyages (excluding
-
in Article 11 of the AFS Convention. The guidelines for conducting these inspections are
described below.
1.2 Ships of 400 gross tonnage and above engaged in international voyages (excluding
fixed or floating platforms, FSUs and FPSOs) will be required to undergo an initial survey
before the ship is put into service or before the International Anti-fouling System
Certificate
(IAFS) is issued for the first time; and a survey should be carried out when the
anti-fouling
systems are changed or replaced.
1.3 Ships of 24 metres in length or more but less than 400 gross tonnage engaged in
international voyages (excluding fixed or floating platforms, FSUs and FPSOs) will have to
carry a Declaration on Anti-fouling Systems signed by the owner or authorized agent. Such
declaration shall be accompanied by appropriate documentation (such as a paint receipt or a
contractor invoice) or contain appropriate endorsement.
2 INITIAL INSPECTION
2.1 Ships required to carry an IAFS Certificate or Declaration on Anti-Fouling
Systems (Parties of the AFS Convention)
2.1.1 The PSCO should check the validity of the IAFS Certificate or Declaration on
-
2 INITIAL INSPECTION
2.1 Ships required to carry an IAFS Certificate or Declaration on Anti-Fouling
Systems (Parties of the AFS Convention)

2.1.1 The PSCO should check the validity of the IAFS Certificate or Declaration on Anti-Fouling Systems, and the attached Record of Anti-Fouling Systems, if appropriate.

2.1.2 The only practical way to apply paint to the ship's bottom (underwater part) is in a dry dock. This means that the date of application of paint on the IAFS Certificate should be checked by comparing the period of dry-docking with the date on the certificate.

2.1.3 If the paint has been applied during a scheduled dry-dock period, it has to be registered in the ship's logbook (in order to be legal). Furthermore, this scheduled dry-docking can be verified by the endorsement date on the (statutory) Safety Construction Certificate (SOLAS, regulation I/10).

2.1.4 In case of an unscheduled dry-dock period, it could be verified by the registration in the ship's logbook (in order to be legal).

2.1.5 It can be additionally verified by the endorsement date on the (Class) Hull Certificate,

-

2.1.4 In case of an unscheduled dry-dock period, it could be verified by the registration in the ship's logbook (in order to be legal).

2.1.5 It can be additionally verified by the endorsement date on the (Class) Hull Certificate,

the dates on the Manufacturer's Declaration or by confirmation of the shipyard.

2.1.6 The IAFS Certificate includes a series of tick boxes indicating:

.1 if an anti-fouling system controlled under Annex 1 of the AFS Convention has or has not been applied, removed or been covered with a sealer coat;

.2 if an anti-fouling system controlled under Annex 1 of the AFS Convention was applied on the ship prior to 1 January 2003 or a later date if specified by the Administration; and

.3 if an anti-fouling system controlled under Annex 1 of the AFS Convention was applied on the ship on/after 1 January 2003 or a later date if specified by the Administration.

2.1.7 Particular attention should be given to verifying that the survey for issuance of the

-

was applied on the ship on/after 1 January 2003 or a later date if specified

b