ions of 11.3.4 and 11.3.5

take into account accuracy information of relevant hydrographic information, as defined by IHO

standards.

11.3.7 It should also be possible to perform a complete route check to support the appraisal

and planning process according to the applicable parts of resolution A.893(21). Detected

objects should be available for review in graphical form and, on demand, in textual form.

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf

objects should be available for review in graphical form and, on demand, in textual form.

11.3.8 It should be possible for the mariner to specify a cross track limit of deviation from the

planned route at which an automatic off-track alarm should be activated.

11.4 Route monitoring

11.4.1 For route monitoring the selected route and own ship's position should appear

whenever the display covers that area.

11.4.2 It should be possible to display a sea area that does not have the ship on the display

(e.g. for look ahead, route planning), while route monitoring. If this is done on the display used

for route monitoring, the automatic route monit oring functions (e.g. updating ship's position,

and providing alerts and indications) should be continuous. It should be possible to return to

the route monitoring display covering own ship's position immediately by single operator action.

11.4.3 It should be possible to select that ECDIS gives an alarm and related graphical

---

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf

11.4.3 It should be possible to select that ECDIS gives an alarm and related graphical

indication if, within a specified time or distance set by the mariner, own ship will pass closer

than a user-selected distance from the safety contour. There should be a permanent indication

when the safety contour alarm is deselected.

11.4.4 ECDIS should give a warning or caution, or indication, as selected by the mariner,

and related graphical indication if, within a specified time or distance set by the mariner, own

ship will pass closer than a user -selected distance from the boundary of a user -selectable

category of prohibited area or of a geographical area for which special conditions exist (see

appendix 4). The user -selectable categories should be the same as user selec tions for the

display of objects and be based on IHO standards. There should be a permanent indication

when any user -selectable categories are deselected. Details of the deselection should be

---

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf

when any user -selectable categories are deselected. Details of the deselection should be

available on demand.

11.4.5 An alarm should be given when the s pecified cross track limit for deviation from the

selected route, if defined by the mariner when route planning, is exceeded.

11.4.6 ECDIS should give a warning or caution or indication as selected by the mariner and

related graphical indication if, continuing on its present course and speed, over a specified

time or distance set by the mariner, own ship will pass closer than a user -specified distance

from a user-selectable category of danger (e.g. obstruction, wreck, rock) that is shallower than

the mariner's safety contour or a user -selectable category of aid to navigation. The

---

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.530(106).pdf

the mariner's safety contour or a user -selectable category of aid to navigation. The

user-selectable categories should be the same as user selections for the display of objects

and be based on IHO standards. There should be a permanent indicatio n when any of the

user-selectable categories are deselected. Details of the deselection should be available on

demand.

11.4.7 A graphical indication should be given if the current or the next leg of the selected

route passes closer than a user-specified distance from the safety contour.

11.4.8 A graphical indication should be given if the current or the next leg of the selected

route goes closer than a user -specified distance from the boundary of a user -selectable

category of prohibited ar ea or a geographic area for which special conditions exist (see

appendix 4). A graphical indication should als