designed and constructed with a view to minimize the uptake and undesirable entrapment of sediments, facilitate removal of sediments, and provide safe access to allow for sediment removal and sampling taking into account the guidelines developed by the Organization,

NOTING FURTHER resolution MEPC.150(55) by which the Committee adopted the Guidelines on design and construction to facilitate sediment control on ships (G12) and resolved to keep these guidelines under review,

HAVING CONSIDERED, at its sixty-third session, a revised text of the Guidelines on design and construction to facilitate sediment control on ships (G12), developed by the Ballast

-

resolved to keep these guidelines under review,

HAVING CONSIDERED, at its sixty-third session, a revised text of the Guidelines on design and construction to facilitate sediment control on ships (G12), developed by the Ballast

Water Review Group of the Committee at its sixty-second session,

1. ADOPTS the 2012 Guidelines on design and construction to facilitate sediment control on ships (G12), as set out in the Annex to this resolution;

2. INVITES Member Governments to apply the 2012 Guidelines (G12) as soon as possible or when the Convention becomes applicable to them; and

3. REVOKES the Guidelines (G12) adopted by resolution MEPC.150(55).

RESOLUTION MEPC.209(63)

Adopted on 2 March 2012

2012 GUIDELINES ON DESIGN AND CONSTRUCTION TO FACILITATE SEDIMENT CONTROL ON SHIPS (G12)MEPC 63/23

Annex 3, page 2

I:\MEPC\63\23.doc

ANNEX

2012 GUIDELINES ON DESIGN AND CONSTRUCTION TO FACILITATE SEDIMENT CONTROL ON SHIPS (G12)

1 PURPOSE

1.1 Regulation B-5.2 of the Convention requires that ships described in regulations B-3.3 to B-3.5 should, without compromising safety or operational efficiency, be designed

-

SEDIMENT CONTROL ON SHIPS (G12)

1 PURPOSE

1.1 Regulation B-5.2 of the Convention requires that ships described in regulations B-3.3 to B-3.5 should, without compromising safety or operational efficiency, be designed

and constructed with a view to minimize the uptake and undesirable entrapment of sediments, facilitate removal of sediments and provide safe access to allow for sediment removal and sampling, taking into account these Guidelines. Ships described in regulation B-3.1 of the Convention should, to the extent practicable, also comply with regulation B-5.2, taking into account these Guidelines.

1.2 The purpose of these Guidelines is to provide guidance to ship designers, shipbuilders, owners and operators in the devel opment of ship structures and equipment to achieve the objectives of paragraph 1.1 and, t hereby, reduce the possibility of

introducing
harmful aquatic organisms and pathogens.
1.3 There may be a conflict between preventing accumulation of sediments and preventing the discharge of harmful aquatic organisms and pathogens.
2 INTRODUCTION
2.1 Water taken up as ships' ballast can contain solid alluvial matter that, once the water
-
preventing the discharge of harmful aquatic organisms and pathogens.
2 INTRODUCTION
2.1 Water taken up as ships' ballast can contain solid alluvial matter that, once the water is becalmed in a ship's ballast tank, will settle out onto the bottom of the tank and other internal structures.
2.2 Aquatic organisms can also settle out of the ballast water and can continue to exist within the sediment. These organisms can surviv e for long periods after the water they were
originally in has been discharged. They may thereby be transported from their natural habitat and discharged in another port or area where they may cause injury or damage to the environment, human health, property and resources.
2.3 Regulation B-5.1 of the Convention requires that all ships remove and dispose of sediments from spaces designated to carry ballast water in accordance with the Ballast Water Management Plans. These Guidelines are to assist ship designers, shipbuilders, owners and operators to design ships to minimize the retention of sediment. Guidance on the management of sediment is contained in the Guidelines for ballast water management
-
owners and operators to design ships to minimize the retention of sediment. Guidance on the management of sediment is contained in the Guidelines for ballast water management and development of ballast water management plans (G4).
3 DEFINITIONS
3.1 For the purposes of these Guidelines, the definitions in the International Convention for the Control and Management of Ships' Ballast Water and Sediments, 2004 (the Convention) apply.
3.2 Ballast water tan