..... .

The sewage treatment plant is certified by the Administration to meet the

effluent standards as provided for in resolution MEPC.2(VI).

The sewage treatment plant is certified by the Administration to meet the

effluent standards as provided for in resolution MEPC.159(55) .

-

effluent standards as provided for in resolution MEPC.2(VI).

The sewage treatment plant is certified by the Administration to meet the

effluent standards as provided for in resolution MEPC.159(55) .

The sewage treatment plant is certified by the Administration to meet the

effluent standards as provided for in the guidelines developed by the

Organization .

Delete as appropriate .

RESOLUTION MEPC.200(62)

Adopted on 15 July 2011

THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF

POLLUTION FROM SHIPS, 1973RESOLUTION MEPC.200(62)

Adopted on 15 July 2011

THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF

POLLUTION FROM SHIPS, 1973

-

RESOLUTION MSC.200(80)

(adopted on 13 May 2005)

ADOPTION OF

RECOMMENDATION ON TESTING OF

LIFE-SAVING APPLIANCESMSC 80/24/Add.1

I:\MSC\80\24-Add-1.doc

ANNEX 17

RESOLUTION MSC.200(80)

(adopted on 13 May 2005)

ADOPTION OF

TESTING OF LIFE-SAVING APPLIANCES

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization

concerning the functions of the Committee,

RECALLING ALSO resolution A.689(17) on Testing of life-saving appliances, by which

the Assembly, at its seventeenth session, adopted recommendations for test requirements for

life-saving appliances,

RECALLING FURTHER that the Assembly, when adopting resolution A.689(17),

authorized the Committee to keep the Recommendation on testing of life-saving appliances
under

review and to adopt, when appropriate, amendments thereto,

NOTING resolution MSC.81(70), by which, at its seventieth session, it adopted the

Revised recommendation on testing of life-saving appliances, recognizing the need to

introduce

-

review and to adopt, when appropriate, amendments thereto,

NOTING resolution MSC.81(70), by which, at its seventieth session, it adopted the

Revised recommendation on testing of life-saving appliances, recognizing the need to introduce

more precise provisions for the testing of life-saving appliances based on the requirements of the

International Life-Saving Appliances (LSA) Code,

BEING DESIROUS to identify and develop comprehensive performance testing and

approval standards for personal life-saving appliances to ensure a good probability of survival for

short duration water immersion,

HAVING CONSIDERED, at its eightieth session,

recommendation on testing of life-saving applia nces, proposed by the Sub-Committee on Ship

Design and Equipment at its forty-eighth session,

1. ADOPTS

appliances (resolution MSC.81(70)), the text of which is set ou t in the Annex to the present

resolution;

2. RECOMMENDS Governments to apply th e annexed amendments when testing

life-saving appliances.

RESOLUTION MSC.200(80)

(adopted on 13 May 2005)

-

resolution;

2. RECOMMENDS Governments to apply th e annexed amendments when testing

life-saving appliances.

RESOLUTION MSC.200(80)

(adopted on 13 May 2005)

ADOPTION OF

RECOMMENDATION ON TESTING OF

LIFE-SAVING APPLIANCESMSC 80/24/Add.1

ANNEX 17

Page 2

I:\MSC\80\24-ADD-1.DOC

ANNEX

THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES

(RESOLUTION MSC.81(70))

PART 1 ■ Prototype tests for life-saving appliances

1 The existing subparagraph .3 of para graph 1.1 is replaced by the following:

■.3 if it is intended to operate the qui ck-release arrangement provided for a self-activated smoke signal and self-igniting light, the lifebuoy has a mass of not less than 4 kg (see 1.8); and■

2 In paragraph 1.2.1.1, the words ■8 h cycle at +65°C■ are replaced by ■8 h exposure at a minimum temperature of +65°C■.

3 In paragraphs 1.2.1.2 and 1.2.1.4, the words ■at a temperature of 20°C – 3°C■ are added after the words ■under ordinary room conditions■.

4 In paragraph 1.2.1.3, the words ■8 h cycle at -30°C■ are replaced by the words ■8 h exposure at a maximum temperature of -30°C■.

-

after the words ■under ordinary room conditions■.