68).pdf

ballast water exchange standard, set out in regulation D-1, or the ballast wat er performance

standard, set out in regulation D -2 of the Convention should be considered as appropriate.

The provisions of the Guidelines for ballast water exchange in the Antarctic treaty area

(resolution MEPC.163(56)) should be taken into consideration , along with other relevant

guidelines developed by the Organization.

4.2 In selecting the ballast water management system, attention should be paid to limiting

conditions specified in the appendix of the Type Approval Certificate and the temperature under

which the system has been tested, in order to ensure its suitability and effectiveness in polar

waters.

4.3 In order to minimize the risk of invasive aquatic species transfers via biofouling,

measures should be considered to minimize the risk of more rapid degradation of anti-fouling

coatings associated with polar ice operations. Reference is made in particular to the

2011 Guidelines for the control and management of ships ' biofouling to minimize the transfer

of invasive aquatic species (resolution MEPC.207(62)).

RESOLUTION MEPC.264(68)

(adopted on 15 May 2015)

-

2011 Guidelines for the control and management of ships ' biofouling to minimize the transfer

of invasive aquatic species (resolution MEPC.207(62)).

RESOLUTION MEPC.264(68)

(adopted on 15 May 2015)

INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 45 -

Table: Example of matters related to anti-fouling systems taken into consideration by

some ice-going ships

(this table is used by some operators of ice-going ships)

Hull Sea chest

Year round

operation in

ice-covered

polar waters

■ Abrasion resistant coating.

■ Compliant with the AFS

Convention. Thickness of

anti-fouling system to be

decided by shipowner.

Intermittent

operation in

ice-covered

polar waters
■ Abrasion resistant low friction
ice coating.
■ In sides, above bilge keel, max
thickness of anti-fouling
system 75 µm, to protect hull
between application of
anti-fouling system and next
anticipated voyage to
ice-covered waters. In bottom
area thickness to be decided
by shipowner. Composition of
anti-fouling system should also
be decided by the shipowner.
■ Compliant with the AFS
Convention. Thickness of
anti-fouling system to be
decided by shipowner.
-
area thickness to be decided
by shipowner. Composition of
anti-fouling system should also
be decided by the shipowner.
■ Compliant with the AFS
Convention. Thickness of
anti-fouling system to be
decided by shipowner.
Category B
and C ships
■ Compliant with the AFS
Convention. Thickness of
anti-fouling system to be
decided by shipowner.
■ Compliant with the AFS
Convention. Thickness of
anti-fouling system to be
decided by shipowner.
RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 46 -
APPENDIX I
Form of Certificate for Ships operating in Polar Waters
POLAR SHIP CERTIFICATE
This Certificate shall be supplemented by a Record of Equipment for the
Polar Ship Certificate

(Official seal)

(State)

Issued under the provisions of the

International Convention for the Safety of Life at Sea, 1974, as amended

under the authority of the Government of

(name of the State)

by _____

(person or organization authorized)

Particulars of ship■

-

under the authority of the Government of

(name of the State)

by _____

(person or organization authorized)

Particulars of ship■

Name of ship…….

Distinctive number or letters……..

Port of registry……..

Gross tonnage……..

IMO number….....

■ Alternatively, the particulars of the ship may be placed horizontally in boxes.

RESOLUTION MEPC.264(68)

(adopted on 15 May 2015)

INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 47 -

THIS IS TO CERTIFY:

1 That the ship has been surveyed in accordance with the applicable safe ty-related provisions of the International Code for Ships Operating in Polar Waters.

2 That the survey showed that the structure, equipment, fittings, radio station arrangements, and materials of the ship and the condition thereof