the appendix.

2 Electric power tables should be validated separately, taking into account the guidelines set out in appendix 2

of the 2014 Guidelines on survey and certification of the Energy Efficiency Design Index (EEDI) (resolution

MEPC.254(67), as amended by resolutions MEPC.261(68) and MEPC.309(73)); consolidated text:

MEPC.1/Circ.855/Rev.2, as may be further amended).

RESOLUTION MEPC.334(76) (adopted on 17 June 2021)

2021 GUIDELINES ON SURVEY AND CERTIFICATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2

Annex 8, page 6

I:\MEPC\76\MEPC 76-15-Add.2.docx

4.2.3 The SFC should be corrected to the value corresponding to the ISO standard reference

conditions using the standard lower calorific value of the fuel oil, referring to ISO 15550:2002 and

ISO 3046-1:2002. For the confirmation of the SFC, a copy of the approved NOX Technical File and

-

conditions using the standard lower calorific value of the fuel oil, referring to ISO 15550:2002 and

ISO 3046-1:2002. For the confirmation of the SFC, a copy of the approved NOX Technical File and

documented summary of the correction calculations should be submitted to the verifier.

4.2.4 For ships equipped with dual-fuel engine(s) using LNG and fuel oil, the CF-factor for gas

(LNG) and the specific fuel consumption (SFC) of gas fuel should be used by applying the criteria

specified in paragraph 4.2.3 of the 2014 Guidelines on survey and certification of the E nergy

Efficiency Design Index (EEDI), as amended,3 as a basis for the guidance of the Administration.

4.2.5 Notwithstanding paragraphs 4.2.3 and 4.2.4, in cases where overridable Shaft / Engine

Power Limitation is installed, or in cases where engines do not have a test report included in the NOX

Technical File, SFC should be calculated in accordance with paragraph 2.2.3 of the EEXI Calculation

Guidelines. For this purpose, actual performance records of the engine may be used if satisfactory

and acceptable to the verifier.

-

Technical File, SFC should be calculated in accordance with paragraph 2.2.3 of the EEXI Calculation

Guidelines. For this purpose, actual performance records of the engine may be used if satisfactory

and acceptable to the verifier.

4.2.6 The verifier may request further information from the submitter, as specified in

paragraph 4.2.7 of the EEDI Survey and Certification Guidelines, in addition to that contained in the

EEXI Technical File, as necessary, to examine the calculation process of the attained EEXI.

4.2.7 In cases where the sea trial report as specified in paragraph 4.2.2.9 is submitted, the verifier should request further information from the submitter to confirm that:

.1 the sea trial was conducted in accordance with the conditions specified in paragraphs 4.3.3, 4.3.4 and 4.3.7 of the EEDI Survey and Certification Guidelines, as applicable;

.2 sea conditions were measured in accordance with ISO 15016:2002 or the equivalent if satisfactory and acceptable to the verifier;

.3 ship speed was measured in accordance with ISO 15016:2002 or the equivalent if satisfactory and acceptable to the verifier; and

-

equivalent if satisfactory and acceptable to the verifier;

.3 ship speed was measured in accordance with ISO 15016:2002 or the equivalent if satisfactory and acceptable to the verifier; and

.4 the measured ship speed was calibrated, if necessary, by taking into account the effects of wind, tide, waves, shallow water and displacement in accordance with ISO 15016:2002 or the equivalent which may be acceptable provided that the concept of the method is transparent for the verifier and publicly available/accessible.

4.2.8 The estimated speed- power curve obtained from the tank test and/or numerical calculations and/or the sea trial results calibrated by the tank test should be reviewed on the basis of the relevant documents in accordance with the EEDI Survey and Certification Guidelines, the defined quality standards (e.g. ITTC 7.5- 03-01-02 and ITTC 7.5-03-01-04 in their latest revisions) and the verification of the numerical set -up with parent hull or the reference set of comparable ships.

4.2.9 I n cases where the overridable Shaft / Engine Power Limitation system is installed,

-

their latest revisions) and the verification of the numerical set -up with parent hull or the reference set of comparable ships.

4.2.9 I n cases where the overridable Shaft / Engine Power Limitation system is installed,

the verifier should confirm that the system is appropriately installed and sealed in accordance with the 2021 Guidelines on the Shaft /