ss (Ce) formula below:

Refer to Definitions for the cost-effectiveness formula in regulation 13.7.5 of the revised MARPOL Annex VI

(MEPC.1/Circ.678).

28 Refer to the 2020 Guidelines for monitoring the worldwide average sulphur content of fuel oils supplied

for use on board ships (resolution MEPC.326(75)).

RESOLUTION MEPC.403(83) (adopted on 11 April 2025)

OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)

Cost of approved method• 10•

Ce =----------

Power (kW) • 0.768 • 6,000 (hours/y ear) · 5 (years) · 6NOx (g/kWh) MEPC 83/17/Add.1

Annex 11, page 30

I:\MEPC\MEPC 83-17-Add.1.docx

.2 the North Sea area as defined in regulation 1.14.6 of Annex V of the present

Convention;

.3 the North American Emission Control Area, which means the area described

by the coordinates provided in appendix VII;

.4 the United States Caribbean Sea Emission Control Area, which means the

area described by the coordinates provided in appendix VII;

.5 the Mediterranean Sea Emission Control Area, which means the area

described by the coordinates provided in appendix VII;

-

area described by the coordinates provided in appendix VII;

.5 the Mediterranean Sea Emission Control Area, which means the area

described by the coordinates provided in appendix VII;

.6 the Canadian Arctic Emission Control Area, which means the area described

by the coordinates provided in appendix VII;

.7 the Norwegian Sea as defined in regulation 13.9.4 of Annex II of the present

Convention; and

.8 the North -East Atlantic Emission Control Area, which means the area

described by the coordinates provided in appendix VII.

4 While a ship is operating within an emission control area, the sulphur content of fuel

oil used on board that ship shall not exceed 0.10% m/m.

5 The sulphur content of fuel oil referred to in paragraph 1 and paragraph 4 of this

regulation shall be documented by its supplier as required by regulation 18 of this Annex.

6 Those ships using separate fuel oils to comply with paragraph 4 of this regulation and

entering or leaving an emission control area set forth in paragraph 3 of this regulation shall

carry a written procedure showing how the fuel oil changeover is to be done, allowing sufficient

-

entering or leaving an emission control area set forth in paragraph 3 of this regulation shall

carry a written procedure showing how the fuel oil changeover is to be done, allowing

sufficient

time for the fuel oil service system to be fully flushed of all fuel oils exceeding the applicable

sulphur content specified in paragraph 4 of this regulation prior to entry into an emission control

area. The volume of low sulphur fuel oils in each tank as well as the date, time and position of

the ship when any fuel oil changeover operation is completed prior to the entry into an emission

control area or commenced after exit from such an area shall be recorded in such logbook or

electronic record book29 as prescribed by the Administration.

7 During the first 12 months immediately following entry into force of an amendment

designating a specific emission control area under paragraph 3 of this regulation, ships

operating in that emission control area are exempt from the requirements in paragraphs 4 and

6 of this regulation and from the requirements of paragraph 5 of this regulation insofar as they

relate to paragraph 4 of this regulation.

-

operating in that emission control area are exempt from the requirements in paragraphs 4 and

6 of this regulation and from the requirements of paragraph 5 of this regulation insofar as they

relate to paragraph 4 of this regulation.

In-use and onboard fuel oil sampling and testing

8 If the competent authority of a Party requires the in -use or onboard sample to be

analysed, it shall be done in accordance with the verification procedure set forth in appendix VI

to determine whether the fuel oil being used or carried for use on board meets the requirements

in paragraph 1 or paragraph 4 of this regulation. The in-use sample shall be drawn taking into

29 Refer to Guidelines for the use of electronic record books under MARPOL (resolution MEPC.312(74)).

account the guidelines developed by the Organization.30 The onboard sample shall be drawn

taking into account the guidelines developed by the Organization.31

-