) , as amended (resolution

MEPC.254(67), as amended).

2.2.3.2 For ships not falling into the scope of the EEDI requirement, the ship speed Vref should

be obtained from an estimated speed-power curve as defined in the 2021 Guidelines on survey

and certification of the attained EEXI (resolution MEPC.334(76)).

-

be obtained from an estimated speed-power curve as defined in the 2021 Guidelines on survey

and certification of the attained EEXI (resolution MEPC.334(76)).

2.2.3.3 For ships not falling into the scope of the EEDI requirement but whose sea trial results,

which may have been calibrated by the tank test, under the EEDI draught and the sea condition

as specified in paragraph 2.2.2 of the EEDI Calculation Guidelines are included in the sea trial

report, the ship speed Vref may be obtained from the sea trial report:

■■■■■■■■ = ■■■■,■■■■■■ ■■ × ■

■■■■■■

■■■■,■■■■■■ ■■

■

1

3

[knot]

RESOLUTION MEPC.333(76) (adopted on 17 June 2021)

2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2

Annex 7, page 5

I:\MEPC\76\MEPC 76-15-Add.2.docx

where,

VS,EEDI, is the sea trial service speed under the EEDI draught; and

PS,EEDI is power of the main engine corresponding to VS,EEDI.

2.2.3.4 For containerships, bulk carriers or tankers not falling into the scope of the EEDI

requirement but whose sea trial results, which may have been calibrated by the tank test, under

-

2.2.3.4 For containerships, bulk carriers or tankers not falling into the scope of the EEDI

requirement but whose sea trial results, which may have been calibrated by the tank test, under

the design load draught and sea condition as specified in paragraph 2.2.2 of the EEDI

Calculation Guidelines are included in the sea trial report, the ship speed Vref may be obtained

from the sea trial report:

■■■■■■■■ = ■■

1

3 × ■■■■■■■■■,■■■■■■■■■■■■■■■

■■■■■■■■■■■■■■■■ ■

2

9

× ■■■■,■■■■ ■■ ■■■■■■■■ × ■ ■■■■■■■■■■,■■■■■■■■■■■■■■■■

1

3

[knot]

where,

VS,service is the sea trial service speed under the design load draught;

DWTS,service is the deadweight under the design load draught;

PS,service is the power of the main engine corresponding to VS,service;

k is the scale coefficient, which should be:

.1 0.95 for containerships with 120,000 DWT or less;

.2 0.93 for containerships with more than 120,000 DWT;

.3 0.97 for bulk carrier with 200,000 DWT or less;

.4 1.00 for bulk carrier with more than 200,000 DWT;

.5 0.97 for tanker with 100,000 DWT or less; and

.6 1.00 for tanker with more than 100,000 DWT.

-

.3 0.97 for bulk carrier with 200,000 DWT or less;

.4 1.00 for bulk carrier with more than 200,000 DWT;

.5 0.97 for tanker with 100,000 DWT or less; and

.6 1.00 for tanker with more than 100,000 DWT.

2.2.3.5 In cases where the speed-power curve is not available or the sea trial report does not

contain the EEDI or design load draught condition, the ship speed V ref can be approximated

by Vref,app to be obtained from statistical mean of distribution of ship speed and engine power,

as defined below:

■■■■■■■■,■■■■■■■ = (■■■■■■■■■,■■■■■■■ – ■■■■■) × ■

∑ ■■■■■■■

0.75×■■■■■■■■■■■■■

■

1

3

[knot]

For LNG carriers having diesel electric propulsion system and cruise passenger ship

having non-conventional propulsion,

■■■■■■■■,■■■■■■■ = (■■■■■■■■■,■■■■■■■ – ■■■■■) × ■

∑ ■■■■■ ■■■■■■■■■■■■■

■■■■■■■■■■■■■

■

1

3

[knot]

where,
Vref,avg is a statistical mean of distribution of ship speed in given ship type and
-
Annex 7, page 6
I:\MEPC\76\MEPC 76-15-Add.2.docx
where,
Vref,avg is a statistical mean of distribution of ship speed in given ship type and
ship size, to be calculated as follows:
■■■■■■■■,■■■■■■■ = ■■ × ■■■■
wher
e
A, B and C are the parameters given in the appendix;
mV is a performance margin of a ship, which should be 5% of Vref,avg
or one knot, whichever is lower; and
MCRavg is a statistical mean of distribution of MCRs for main engines and
MPPavg is a statistical mean of distribution of MPPs for motors in given ship
type and ship size, to be calculated as follows:
■■■■■■■■■■■■■■■■■ ■■■■■■■■■■■■■ = ■■ × ■■■■
wher
e
D, E and F are the parameters given in the appendix;
In cases where the overridable Shaft / Engine Power Limitation is installed, the ship
speed Vref approximated by Vref,app should be