"EEDI" should be read as "EEXI".

2.2.1 PME(i) ; Power of main engines

In cases where overridable Shaft / Engine Power Limitation is installed in accordance with

the 2021 Guidelines on the shaft / engine power limit to comply with the EEXI requirements

and use of a power reserve (resolution MEPC.335(76)), PME(i) is 83% of the limited installed

power (MCRlim) or 75% of the original installed power (MCR), whichever is lower, for each main

engine (i). In cases where the overridable Shaft / Engine Power Limitation and shaft

generator(s) are installed, in referring to paragraph 2.2.5.2 (option 1) of the EEDI Calculation

Guidelines, "MCRME" should be read as "MCRlim".

engine (i). In cases where the overridable Shaft / Engine Power Limitation and shaft

generator(s) are installed, in referring to paragraph 2.2.5.2 (option 1) of the EEDI Calculation

Guidelines, "MCRME" should be read as "MCRlim".

For LNG carriers having steam turbine or diesel electric propulsion, PME(i) is 83% of the limited

installed power (MCRlim, MPPlim), divided by the electrical efficiency in case of diesel electric

propulsion system, for each main engine (i). For LNG carriers, the power from combustion of

( )

mrefwl c i

nef

f

i

MEFMEieffieffAEFAE

nPTI

i

neff

i

iAEeffieffiPTI

n

j

jAEFAEAEiMEiFME

nME

i

iME

n

j

j

f V fCapacity f f f

SFC C P fSFC C P f P fSFC C PSFC C P f

. . . . . .

$$\left(\sum_{i=1}^{n_{ME}} P_{ME(i)} \cdot C_{FME(i)} \cdot SFC_{ME(i)} + \left(\sum_{j=1}^{n_{AE}} P_{AE(j)} \cdot C_{FAE(j)} \cdot SFC_{AE(j)}\right) + \left(\sum_{k=1}^{n_{PTI}} P_{PTI(k)} \cdot C_{FME(k)} \cdot SFC_{ME(k)}\right) - \left(\sum_{l=1}^{n_{eff}} P_{eff(l)} \cdot C_{FME(l)} \cdot SFC_{ME(l)}\right) + \left(\sum_{i=1}^{n_{ME}} P_{ME(i)} \cdot C_{FME(i)} \cdot SFC_{ME(i)}\right) \cdot \left(\sum_{c=1}^{n_{refwl}} P_{mref(c,i)} \cdot C_{FME(i)} \cdot SFC_{ME(i)}\right)\right)$$

( ) (1 1) () () (1) () (1) (1

RESOLUTION MEPC.333(76) (adopted on 17 June 2021)

2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2

Annex 7, page 4

I:\MEPC\76\MEPC 76-15-Add.2.docx

the excessive natural boil-off gas in the engines or boilers to avoid releasing to the atmosphere

-

Annex 7, page 4

I:\MEPC\76\MEPC 76-15-Add.2.docx

the excessive natural boil-off gas in the engines or boilers to avoid releasing to the atmosphere

or unnecessary thermal oxidation should be deducted from PME(i) with the approval of the verifier.

2.2.2 PAE(i) ; Power of auxiliary engines

2.2.2.1 PAE(i) is calculated in accordance with paragraph 2.2.5.6 of the EEDI Calculation Guidelines.

2.2.2.2 For ships where power of auxiliary engines (PAE) value calculated by paragraphs 2.2.5.6.1 to 2.2.5.6.3 of the EEDI Calculation Guidelines is significantly diff erent from the total power used at normal seagoing, e.g. in cases of passenger ships, the PAE value should be estimated by the consumed electric power (excluding propulsion) in conditions when the ship is engaged in a voyage at reference speed (Vref) as given in the electric power table, divided by the average efficiency of the generator(s) weighted by power (see appendix 2 of the EEDI Calculation Guidelines).

2.2.2.3 In cases where the electric power table is not available, the P AE value may be approximated either by:

.1 annual average figure of P AE at sea from onboard monitoring obtained prior

-

EEDI Calculation Guidelines).

2.2.2.3 In cases where the electric power table is not available, the P AE value may be approximated either by:

.1 annual average figure of P AE at sea from onboard monitoring obtained prior to the EEXI certification;

.2 for cruise passenger ships, approximated value of power of auxiliary engines (PAE,app), as defined below:

■■■■■■,■■■■■■ = 0.1193 × ■■■■ + 1814.4 [kW]

.3 for ro-ro passenger ships, approximated value of power of auxiliary engines (PAE,app), as defined below:

■■■■■■,■■■■■■ = 0.866 × ■■■■0.732 [kW]

2.2.3 Vref ; Ship speed

2.2.3.1 For ships falling into the scope of the EEDI requirement, the ship speed V ref

should

be obtained from an approved speed-power curve as defined in the 2014 Guidelines on survey

and certification of the Energy Efficiency Design Index (EEDI) , as amended (resolution

MEPC.254(67), as amended).

2.2.3.2 For ships not falling into the scope of the EEDI requirement, the ship speed Vref
should

be obtained from an estimated speed-power curve as defined in the 2021 Guidelines on survey

and certification of the attained EEXI (resolution MEPC.334(76)).

-

be obtained from an estimated speed-power curve as defined in the 2021 Guidelines on survey

and certification of the attained EEXI (resolution MEPC.334(76)).

2.2.3.3 For ships not falling into the scope of the EEDI requirement but whose sea trial
results,

which may have been calibrated by the tank test, under the EEDI draught and the sea
condition

as specified in paragraph 2.2.2 of the EEDI Calculation Guidelines are included in the sea
tri