–0.23) g/kWh when n is 130 or more but less than 2,000 rpm; and

.3 7.7 g/kWh when n is 2,000 rpm or more.

22 Refer to the 2024 Guidelines as required by regulation 13.2.2 of MARPOL Annex VI in respect of

non-identical replacement engines not required to meet the Tier III limit (resolution MEPC.386(81)).

23 Refer to the Guidelines for the application of the NOx Technical Code relative to certification and amendments

of Tier I engines (MEPC.1/ Circ.679).

RESOLUTION MEPC.403(83) (adopted on 11 April 2025)

-

23 Refer to the Guidelines for the application of the NOx Technical Code relative to certification and amendments

of Tier I engines (MEPC.1/ Circ.679).

RESOLUTION MEPC.403(83) (adopted on 11 April 2025)

OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1

Annex 11, page 25

I:\MEPC\MEPC 83-17-Add.1.docx

Tier III

5.1 Subject to regulation 3 of this Annex, in an emission control area designated for Tier III

NOx control under paragraph 6 of this regulation (NO x Tier III emission control area), the

operation of a marine diesel engine that is installed on a ship is prohibited:

.1 except when the emission of nitrogen oxides (calculated as the total weighted

emission of NO 2) from the engine is within the following limits, where

n = rated engine speed (crankshaft revolutions per minute):

.1 3.4 g/kWh when n is less than 130 rpm;

.2 9 n(–0.2) g/kWh when n is 130 or more but less than 2,000 rpm;

.3 2.0 g/kWh when n is 2,000 rpm or more;

when

.2 that ship is constructed on or after:

.1 1 January 2016 and is operating in the North American Emission

-

.2 9 n(–0.2) g/kWh when n is 130 or more but less than 2,000 rpm;

.3 2.0 g/kWh when n is 2,000 rpm or more;

when

.2 that ship is constructed on or after:

.1 1 January 2016 and is operating in the North American Emission

Control Area or the United States Caribbean Sea Emission Control

Area;

.2 1 January 2021 and is operating in the Baltic Sea Emission Control

Area or the North Sea Emission Control Area;

.3 1 March 2026 and is operating in the Norwegian Sea Emission

Control Area. For the Norwegian Sea Emission Control Area, "ship

constructed on or after 1 March 2026" means a ship:

.1 for which the building contract is placed on or after 1 March 2026; or

.2 in the absence of a building contract, the keel of which is laid or which is at a similar stage of construction on or after 1 September 2026; or

.3 the delivery of which is on or after 1 March 2030.

when

.3 that ship is operating in a NO x Tier III emission control area other than an emission control area described in paragraph 5.1.2 of this regulation, and is constructed on or after the date of adoption of such an emission control area,

-

when

.3 that ship is operating in a NO x Tier III emission control area other than an emission control area described in paragraph 5.1.2 of this regulation, and is constructed on or after the date of adoption of such an emission control area, or a later date as may be specified in the amendment d esignating the NOx Tier III emission control area, whichever is later:

.1 that ship is constructed on or after 1 January 2025 and is operating in the Canadian Arctic Emission Control Area;

.2 that ship is constructed on or after 1 January 2027 and is operating in the North-East Atlantic Emission Control Area. For the North-East Atlantic Emission Control Area, "ship constructed on or after 1 January 2027" means a ship:

.1 for which the building contract is placed on or after 1 January 2027; or

.2 in the absence of a building contract, the keel of which is laid or which is at a similar stage of construction on or after 1 July 2027; or

-

.1 for which the building contract is placed on or after 1 January 2027; or

.2 in the absence of a building contract, the keel of which is laid or which is at a similar stage of construction on or after 1 July 2027; or

.3 the delivery of which is on or after 1 January 2031.

5.2 The standards set forth in paragraph 5.1.1 of this regulation shall not apply to:

.1 a marine diesel engine installed on a ship with a length (L), as defined in regulation 1.19 of Annex I to the present Convention, of less than 24 metres when it has been specifically designed, and is used solely, for rec