rt system should be capable of being tested.

***

RESOLUTION MSC.136(76)

(adopted on 11 December 2002)

PERFORMANCE STANDARDS FOR A SHIP

SECURITY ALERT SYSTEMRESOLUTION MSC.136(76)

(adopted on 11 December 2002)

PERFORMANCE STANDARDS FOR A SHIP

SECURITY ALERT SYSTEM

-

RESOLUTION MSC.137(76)

(adopted on 4 December 2002)

STANDARDS FOR SHIP MANOEUVRABILITYMSC 76/23/Add.1

I:\MSC\76\23-ADD.1.DOC

ANNEX 6

RESOLUTION MSC.137(76)

(adopted on 4 December 2002)

STANDARDS FOR SHIP MANOEUVRABILITY

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO that by resolution A.751(18) the Assembly approved Interim Standards for ship manoeuvrability (the Interim standards), whereby Governments were recommended to encourage those responsible for the design, construction, repair and operation of ships to apply the Interim Standards and invited to collect data obtained by the application of the Interim Standards and report them to the Organization,

RECALLING FURTHER that by circular MSC/Circ.1053 the Committee approved Explanatory notes to the Standards for ship manoeuvrability, to provide Administrations with specific guidance so that adequate data may be collected by the Organization on the manoeuvrability of ships,

RECOGNIZING the manoeuvring capability of ship s to be an important contribution to

-

specific guidance so that adequate data may be collected by the Organization on the manoeuvrability of ships,

RECOGNIZING the manoeuvring capability of ship s to be an important contribution to the safety of navigation,

BELIEVING that the development and im plementation of standards for ship manoeuvrability, particularly for large ships and ships carrying dangerous goods in bulk, will improve maritime safety and enhance marine environmental protection,

HAVING CONSIDERED the recommendation made by the Sub-Committee on Ship Design and Equipment at its forty-fifth session,

1. ADOPTS the Standards for ship manoeuvrabilit y, the text of which is set out in the

Annex to the present resolution;

2. INVITES Governments to encourage those re sponsible for the design, construction, repair

and operation of ships to apply the Standards to ships constructed on or after 1 January 2004;

3. RESOLVES that the provisions annexed to the present resolution supersede the

provisions annexed to resolution A.751(18).

RESOLUTION MSC.137(76)

(adopted on 4 December 2002)

STANDARDS FOR SHIP MANOEUVRABILITYMSC 76/23/Add.1

ANNEX 6

Page 2

I:\MSC\76\23-ADD.1.DOC

-

provisions annexed to resolution A.751(18).

RESOLUTION MSC.137(76)

(adopted on 4 December 2002)

STANDARDS FOR SHIP MANOEUVRABILITYMSC 76/23/Add.1

ANNEX 6

Page 2

I:\MSC\76\23-ADD.1.DOC

ANNEX

STANDARDS FOR SHIP MANOEUVRABILITY

1 P RINCIPLES

1.1 The Standards for ship manoeuvrability (the St andards) should be used to evaluate the

manoeuvring performance of ships and to assist those responsible for the design, construction,

repair and operation of ships.

1.2 It should be noted that the Standards were developed for ships with traditional propulsion

and steering systems (e.g. shaft driven ships w ith conventional rudders). Therefore, the

Standards and methods for establishing compliance may be periodically reviewed and updated by

the Organization, as appropriate, taking in to account new technologies, research and

development, and the results of experience with the present Standards.

2 G ENERAL

2.1 The Standards contained in this document are based on the understanding that the

manoeuvrability of ships can be evaluated from the characteristics of conventional trial manoeuvres.

-

2 G ENERAL

2.1 The Standards contained in this document are based on the understanding that the

manoeuvrability of ships can be evaluated from the characteristics of conventional trial manoeuvres.

The following two methods can be used to demonstrate compliance with these Standards:

.1 scale model tests and/or computer pred ictions using mathematical models can be

performed to predict compliance at the design stage. In this case full-scale trials

should be conducted to validate these results . The ship should then be considered to meet these Standards regardless of full-scale trial results, except where the Administration determines that the prediction efforts were substandard and/or the ship performance is in substantial disagreement with these Standards; and

.2 the compliance with the Standards can be dem