otherwise, for ships constructed before 1 January 2009,
the Administration shall ensu re that the requirements which are applicable under
chapter II-1 of the Internat ional Convention for the Safety of Life at Sea, 1974, as
amended by resolutions MSC.1(XLV) , MSC.6(48), MSC.11(55), MSC.12(56),
MSC.13(57), MSC.19(58), MSC.26(60), MSC.27(61), Resolution 1 of the 1995 SOLAS
Conference, MSC.47(66), MSC.57(67), MSC.65(68), MSC.69(69), MSC.99(73),
MSC.134(76), MSC.151(78) and MSC.170(79) are complied with.

3 All ships which undergo repairs, alterati ons, modifications a nd outfitting related
thereto shall continue to comply with at least the requirements previously applicable to
these ships. Such ships, if constructed before the date on which any relevant amendments
-
thereto shall continue to comply with at least the requirements previously applicable to
these ships. Such ships, if constructed before the date on which any relevant amendments
enter into force, shall, as a rule, comply w ith the requirements for ships constructed on
or
after that date to at least the same extent as they did before undergoing such repairs,
alterations, modifications or out fitting. Repairs, alterations and modifications of a
major
character and outfitting related thereto shall meet the requirements for ships constructed
on or after the date on which any relevant amendments enter into force, in so far as the
Administration deems reasonable and practicable.

4 The Administration of a State may, if it considers that the sheltered nature and
conditions of the voyage are such as to render the application of any specific requirements
of this chapter unreasonable or unnecessary, exempt from those requirements individual
-
conditions of the voyage are such as to render the application of any specific requirements
of this chapter unreasonable or unnecessary, exempt from those requirements individual
ships or classes of ships entitled to fly the flag of that State which, in the course of
their
voyage, do not proceed more than 20 miles from the nearest land.

5 In the case of passenger ships which are employed in special trades for the
carriage of large numbers of special trade pa ssengers, such as the pilgrim trade, the
Administration of the State whose flag such ship s are entitled to fly, if satisfied that
it is
impracticable to enforce compliance with the requirements of this chapter, may exempt
such ships from those requirements, prov ided that they comply fully with the
provisions of:

.1 the rules annexed to the Special Trade Passenger Ships Agreement, 1971;
and

.2 the rules annexed to the Protocol on Space Requirements for Special Trade
Passenger Ships, 1973.

Regulation 2

-
and
.2 the rules annexed to the Protocol on Space Requirements for Special Trade

Passenger Ships, 1973.

Regulation 2

Definitions

For the purpose of this chapter, unless expressly provided otherwise:

1 Subdivision length (Ls) of the ship is the greatest pr ojected moulded length of that part of the ship at or below deck or decks limiting the vertical extent of flooding with the ship at the deepest subdivision draught.

2 Mid-length is the mid-point of the subdivision length of the ship.

3 Aft terminal is the aft limit of the subdivision length.

4 Forward terminal is the forward limit of the subdivision length.

5 Length (L) is the length as defined in the In ternational Convention on Load Lines in force.

RESOLUTION MSC.216(82)

(adopted on 8 December 2006)

6 Freeboard deck is the deck as defined in the International Convention on Load Lines in force.

-

6 Freeboard deck is the deck as defined in the International Convention on Load Lines in force.

7 Forward perpendicular is the forward perpendicular as defined in the International Convention on Load Lines in force.

8 Breadth (B) is the greatest moulded breadth of the ship at or below the deepest subdivision draught.

9 Draught (d) is the vertical distance from th e keel line at mid-length to the waterline in question.

10 Deepest subdivision draught (d s) is the waterline which corresponds to the summer load line draught of the ship.

11 Light service draught (d l) is the service draught co rresponding to the lightest anticipated loading and associated tankage, including, however, such ballast as may be necessary for stability and/ or immersion. Passenger ship s should include the full complement of passengers and crew on board.

12 Partial subdivision draught (