channels used for AIS in their waters.

***

RESOLUTION MSC.140(76)

(adopted on 5 December 2002)

RECOMMENDATION FOR THE PROTECTION

OF THE AIS VHF DATA LINKRESOLUTION MSC.140(76)

(adopted on 5 December 2002)

RECOMMENDATION FOR THE PROTECTION

OF THE AIS VHF DATA LINK

-

RESOLUTION MSC.141(76)

(adopted on 5 December 2002)

REVISED MODEL TEST METHOD UNDER RESOLUTION 14

OF THE 1995 SOLAS CONFERENCE

ANNEX 17

RESOLUTION MSC.141(76)

(adopted on 5 December 2002)

REVISED MODEL TEST METHOD UNDER RESOLUTION 14

OF THE 1995 SOLAS CONFERENCE

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 38(c) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO resolution 14 on Regi onal agreements on specific stability requirements for ro-ro passenger ships, adopted by the Conference of C ontracting Governments to the International Convention for the Sa fety of Life at S ea, 1974 (the 1995 SOLAS Conference),

NOTING that resolution 14 of the 1995 SOLA S Conference includes an option whereby the Administration may, as an alternative to calculation of the stability properties of a ship,

accept model tests carried out for an individual ship in accordance with the model test method developed by the Organization, as appended to the Annex to the said resolution,

-

accept model tests carried out for an individual ship in accordance with the model test method developed by the Organization, as appended to the Annex to the said resolution,

BEING AWARE of the experience gained from model tests carried out in the past by Administrations using the aforementioned model test method,

BEARING IN MIND the compelling need to keep pace with new technology and knowledge,

HAVING CONSIDERED the recommendation made by the Sub-Committee on Stability and Load Lines and on Fishing Vessels Safety at its forty-fifth session,

1. ADOPTS the Revised Model Test Method under resolution 14 of the 1995 SOLAS

Conference, including the associated Guidance Notes appended thereto, the text of which is set

out in the Annex to the present resolution;

2. INVITES Member Governments which are party to regional agreements under

resolution 14 of the 1995 SOLAS Conference to use the annexed Revised Model Test Method

and associated Guidance Notes in lieu of the or iginal model test method appended to the said

resolution.

RESOLUTION MSC.141(76)

(adopted on 5 December 2002)

REVISED MODEL TEST METHOD UNDER RESOLUTION 14

-

and associated Guidance Notes in lieu of the or iginal model test method appended to the said

resolution.

RESOLUTION MSC.141(76)

(adopted on 5 December 2002)

REVISED MODEL TEST METHOD UNDER RESOLUTION 14

OF THE 1995 SOLAS CONFERENCEMSC 76/23/Add.1

ANNEX 17

Page 2

I:\MSC\76\23-ADD.1.DOC

ANNEX

REVISED MODEL TEST METHOD

1 Objectives

This revised model test method is a revision of the method contained in the Appendix to

the Annex to resolution 14 of the 1995 SOLAS Conf erence. Since the entry into force of the

Stockholm Agreement a number of model tests has been carried out in accordance with the test

method previously in force. During these tests a number of refinements in the procedures have

been identified. This new model test method aims to include these refinements and, together

with the appended Guidance Notes, provide a more robust procedure for the assessment of

survivability of a damaged ro-ro passenger ship in a seaway. In this respect, the model should

prove capable of withstanding the seaway define d in paragraph 4 below, in the worst damage

case scenario.

2 Definitions

L BP is the length between perpendiculars

-

prove capable of withstanding the seaway define d in paragraph 4 below, in the worst damage

case scenario.

2 Definitions

L BP is the length between perpendiculars

H S is the significant wave height

B is the moulded breadth of the ship

T P is the peak period

T Z is the zero crossing period

3 Ship model

3.1.1 The model should copy the actual ship for both outer configuration and internal arrangement ■ in particular all damaged spaces having an effect on the process of flooding and shipping of water. Intact dr aught, trim, heel and limiting operational KG corresponding to the worst damage case should be used. Furthermore, the test case(s) to be considered should represent the worst damage case(s) defined in accordance with SOLAS regulation II-1/8.2.3.2 (SOLAS 90) with regard to the total area under the positive GZ curve and the centreline of the