2024)

FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

NOTING resolution MSC.391(95), by which it adopted the International Code of Safety for Ships using Gases or other Low -flashpoint Fuels (IGF Code), which has become mandatory under chapter II -1 of the International Convention for the Safety of Life at Sea, 1974 ("the Convention"), and subsequent amendments adopted to the IGF Code,

NOTING ALSO article VIII(b) and regulation II -1/2.28 of the Convention concerning the procedure for amending the IGF Code,

---

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf

NOTING ALSO article VIII(b) and regulation II -1/2.28 of the Convention concerning the procedure for amending the IGF Code,

HAVING CONSIDERED, at its 109th session,

circulated in accordance with article VIII(b)(i) of the Convention:

1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amendments to the IGF Code, the text of which is set out in the annex to the present resolution;

2 DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that the said amendments shall be deemed to have been accepted on 1 July 2027, unless, prior to that date, more than one third of the Contracting Governments to the Convention or Contracting Governments the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet have notified the Secretary -General of their objections

to the amendments;

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf

tonnage of the world's merchant fleet have notified the Secretary -General of their objections

to the amendments;

3 INVITES Contracting Governments to the Convention to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 January 2028 upon their acceptance in accordance with paragraph 2 above;

4 REQUESTS the Secretary -General, for the purposes of article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention;

5 ALSO REQUESTS the Secretary-General to transmit copies of this resolution and its annex to Members of the Organization which are not Contracting Governments to the Convention.

RESOLUTION MSC.567(109) (adopted on 6 December 2024)

FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

ANNEX

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf

FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

ANNEX

FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE)

PART A

2 General

2.2 Definitions

1 The following new paragraph 2.2.44 is added after paragraph 2.2.43:

"2.2.44 Ship constructed on or after 1 January 2028 means:

.1 for which the building contract is placed on or after 1 January 2028;

or

.2 in the absence of a building contract, the keels of which are laid or which are at a similar stage of construction on or after 1 July 2028;

or

.3 the delivery of which is on or after 1 January 2032."

PART A-1

Specific requirements for ships using natural gas as fuel

5 Ship design and arrangement

5.3 Regulations – General

2 The following new paragraph 5.3.3.5.1 is inserted after paragraph 5.3.3.5 and before paragraph 5.3.3.6:

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf

5.3 Regulations – General

2 The following new paragraph 5.3.3.5.1 is inserted after paragraph 5.3.3.5 and before paragraph 5.3.3.6:

"5.3.3.5.1 For ships with suction wells installed in fuel tanks, the bottom of the suction well may protrude into the vertical extent of the minimum distance specified in 5.3.3.5, provided that such wells are as small as practicable and the protrusion below the inner bottom plating does not exceed 25% of the depth of the double bottom or 350 mm, whichever is less."

3 In sub-paragraph 5.3.4.2, the definition of "H" is replaced by the following:

"H is the distance from baseline, in metres, to the lowermost