he Committee to keep the annexed Recommendation on
testing of life -saving appliances under review and to adopt, when appropriate, amendments
thereto,
RECALLING FURTHER that, since the adoption of resolution A.689(17), the Committee has
amended the Recommendation annexed thereto by resolutions MSC.54(66) and MSC.81(70),
---
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.563(108).pdf
amended the Recommendation annexed thereto by resolutions MSC.54(66) and MSC.81(70),
and by circulars MSC/Circ.596, MSC/Circ.615 and MSC/Circ.809,
RECOGNIZING the need to ensure that the references in the Revised recommendation on
testing of life-saving appliances (resolution MSC.81(70)) are kept up to date,
1 ADOPTS the
appliances (MSC.81(70)), set out in the annex to the present resolution;
2 RECOMMENDS that Governments apply the amendments when testing life-saving
appliances, as set out in the annex to the present resolution;
3 INVITES Contracting Governments to the SOLAS Convention to bring the above
RESOLUTION MSC.563(108) (adopted on 23 May 2024)
TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))
MSC 108/20/Add.1
Annex 15, page 2
I:\MSC\108\MSC 108-20-Add.1.docx
ANNEX

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.563(108).pdf
TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))
MSC 108/20/Add.1
Annex 15, page 2
I:\MSC\108\MSC 108-20-Add.1.docx
ANNEX
TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))
PART 1 - PROTOTYPE TEST FOR LIFE-SAVING APPLIANCES
2.8 Water performance tests
Test subjects
1 The following new paragraph 2.8.2.1 is added after existing paragraph 2.8.2:
"2.8.2.1 If a "no turn" is recorded for a test subject wearing the RTD during the righting
tests in 2.8.5, the test subject may be replaced with one additional test subject from
the same height and weight category and in accordance with 2.7.2."
Assessment
2 Paragraph 2.8.7.1 is replaced by the following:
"2.8.7 After the water tests described in 2.8.5 and .6 above:
.1 Turning time: The average turn time for all subjects in the candidate
lifejacket should not exceed the average time in the RTD plus 1 s,

---
URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.563(108).pdf
.1 Turning time: The average turn time for all subjects in the candidate
lifejacket should not exceed the average time in the RTD plus 1 s,
and at the end of each righting test, each test subject should attain
a face-up position where the nose and mouth are clear of the water;
.2 Freeboard: The average freeboard of all the subjects should not be
less than the average for the RTD minus 10 mm;
.3 Torso angles: The average of all subjects' torso angles should be
not less than the average for the RTD minus 10°;
.4 Faceplane (head) angles : The average of all subjects ' faceplane
angles should be not less than the average for the RTD minus 10°;
and
.5 Lifejacket light location : The position of the lifejacket light should
permit it to be visible over as great a segment of the upper
hemisphere as is practicable."
RESOLUTION MSC.563(108) (adopted on 23 May 2024)
TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.563(108).pdf
TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70))

PART 2 - PRODUCTION AND INSTALLATION TESTS
6.1 Launching appliances using falls and winches
Installation tests
Loaded test
3 Paragraph 6.1.2 is replaced by the following:
"6.1.2 The survival craft or rescue boat, loaded with its normal equipment or an
equivalent mass and a distributed mass equivalent to that of the number of persons,
each weighing 75 kg or 82.5 kg, as applicable, it is permitted to accommodate, should
be released by o peration of the launching control on deck. The speed at which the
survival craft or rescue boat is lowered into the water should be not less than that
obtained from the formula:
S = 0.4 + 0.02H, or 1.0, whichever is less
where: S = speed of lowering (m/s)
H = height from davit head to the waterline at the lightest seagoing condition
(m).

SOURCE: MSC.563(108).p