).pdf

The vacuum insulation evaluation should be specified for the normal range or upper limit of cold

vacuum pressure (CVP), and loss of vacuum should be defined with respect to this value.

Accordingly, effect of vacuum pressure should be taken into account at the time of design and

---

URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.572(110).pdf

RESOLUTION MSC.572(110) (adopted on 26 June 2025)

INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974

RESOLUTION MSC.572(110)

(adopted on 26 June 2025)

INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization

concerning the functions of the Committee,

RECALLING ALSO article VIII(b) of the International Convention for the Safety of Life at

Sea, 1974 ("the Convention"), concerning the amendment procedure applicable to the annex

to the Convention, other than to the provisions of chapter I,

HAVING CONSIDERED, at its 110th session,

circulated in accordance with article VIII(b)(i) of the Convention,

1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention,

---

URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.572(110).pdf

1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention,

the Convention, the text of which is set out in the annex to the present resolution;

2 DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that

the said amendments shall be deemed to have been accepted on 1 July 2027, unless, prior to

that date, more than one third of the Contracting Governments to the Convention or

Contracting Governments the combined merchant fleets of which constitute not less than 50%

of the gross tonnage of the world's merchant fleet have notified the Secretary-General of their

objections to the amendments;

3 INVITES Contracting Governments to the Convention to note that, in accordance

with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force

on 1 January 2028 upon their acceptance in accordance with paragraph 2 above;

4 REQUESTS the Secretary -General, for the purposes of article VIII(b)(v) of

---

URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.572(110).pdf

4 REQUESTS the Secretary -General, for the purposes of article VIII(b)(v) of

the Convention, to transmit certified copies of the present resolution and the text of

the amendments contained in the annex to all Contracting Governments to the Convention;

5 ALSO REQUESTS the Secretary -General to transmit copies of this resolution and its annex to Members of the Organization which are not Contracting Governments to the Convention.

RESOLUTION MSC.572(110) (adopted on 26 June 2025)

INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974

ANNEX

SAFETY OF LIFE AT SEA, 1974

CHAPTER II-2

CONSTRUCTION – FIRE PROTECTION, FIRE DETECTION AND FIRE EXTINCTION

Part C

Suppression of fire

Regulation 11

Structural integrity

2 Material of hull, superstructures, structural bulkheads, decks and deckhouses

1 Section 2 is replaced by the following:

URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.572(110).pdf

Structural integrity

2 Material of hull, superstructures, structural bulkheads, decks and deckhouses

1 Section 2 is replaced by the following:

"2 Material of hull, superstructures, structural bulkheads, decks and deckhouses

The hull, superstructures, structural bulkheads, decks and deckhouses shall be constructed of steel or other equivalent material. For the purpose of applying the definition of steel or other equivalent material as given in regulation 3.43, the "applicable fire exposure" shall be according to the integrity and insulation standards given in tables 9.1 to 9.8. For example, where divisions such as decks or sides and ends of deckhouses are permitted to have "B -0" fire integrity, the "applicable fire exposure" shall be half an hour."

4 Machinery spaces of category A

4.1 Crowns and casings

2 Paragraph 4.1 is replaced by the following:

"4.1 Crowns and casings

Crowns and casings of machinery spaces of category A shall be of steel construction

---

URL: https://wwwcdn.imo.org/localresou