,

RECALLING ALSO resolution A.886(21), by which the Assembly resolved that the functions of adopting performance standards and technical specifications, as well as amendments thereto, shall be performed by the Maritime Safety Committee on behalf of the Organization,

RECALLING FURTHER resolution MSC.74(69), annex 3, by which the Committee adopted the Recommendation on performance standards for a universal automatic identification system

---

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf

the Recommendation on performance standards for a universal automatic identification system (AIS) to improve the safety of navigation,

TAKING INTO ACCOUNT resolution A.1192(33), by which the Assembly urged Member States and all relevant stakeholders to promote actions to prevent illegal operations in the maritime sector by the "dark fleet" or "shadow fleet",

RECOGNIZING the need for measures to prevent unauthorized entry or tampering of the ship's identity information in shipborne automatic identification systems (AIS),

HAVING CONSIDERED, at its 109th session, the recommendation made by the Sub-Committee on Navigation, Communications and Search and Rescue at its eleventh session,

1 ADOPTS revised Performance standards for a universal shipborne automatic identification system (AIS), set out in the annex to the present resolution;

2 RECOMMENDS that Governments ensure that AIS equipment conforms to performance standards not inferior to those specified in:

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf

2 RECOMMENDS that Governments ensure that AIS equipment conforms to performance standards not inferior to those specified in:

.1 the present resolution if the equipment is installed on:

.1 new ships for which the building contract is placed on or after 1 January 2029, or in the absence of the contract, the keel of which is laid or which are at a similar stage of construction on or after 1 January 2029; or

.2 ships other than those ships prescribed in sub-paragraph .1 above, all installations of the specified type, having a contractual delivery date on or after 1 January 2029, or in the absence of a contractual delivery date to the ship, actually delivered to the ship on or after 1 January 2029; or

.2 annex 3 to resolution MSC.74(69) if the equipment is installed on ships other than those prescribed in paragraph 2.1 above.

RESOLUTION MSC.570(109) (adopted on 6 December 2024)

PERFORMANCE STANDARDS FOR A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS)

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf

RESOLUTION MSC.570(109) (adopted on 6 December 2024)

PERFORMANCE STANDARDS FOR A UNIVERSAL

SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS)

MSC 109/22/Add.1

Annex 23, page 2

I:\MSC\109\22\MSC 109-22-Add.1.docx

ANNEX

PERFORMANCE STANDARDS FOR

A UNIVERSAL SHIPBORNE AUTOMATIC IDENTIFICATION SYSTEM (AIS)

1 Scope

1.1 These performance standards specify the requirements for the universal AIS.

1.2 The AIS should improve the safety of navigation by assisting in the efficient navigation

of ships, protection of the environment, and operation of vessel traffic services (VTS),

by satisfying the following functional requirements:

.1 in a ship-to-ship mode for collision avoidance;

.2 as a means for littoral States to obtain information about a ship and its cargo;

and

.3 as a VTS tool, i.e. ship-to-shore (traffic management).

1.3 The AIS should be capable of providing to ships and to competent authorities

---

URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.570(109).pdf

.3 as a VTS tool, i.e. ship-to-shore (traffic management).

1.3 The AIS should be capable of providing to ships and to competent authorities

information from the ship, automatically and with the required accuracy and frequency, to

facilitate accurate tracking. Transmission of the data should be with the minimum involvement

of a ship's personnel and with a high level of availability.

1.4 The installation, in addition to meeting the requirements of the Radio Regulations,

applicable ITU -R Recommendations and the general requirements as set out in

resolution A.694(17), should comply with the following performance standards.

2 Functionality

The system should be capable of operating in a number of modes:

.1 an "autonomous and continuous" mode for operation in all areas. This mode

should be capable of being switched to/from one of the follo