subjected to the greater of the heeling moments in 1.1.2 and 1.1.4 of that annex.

2.3.2 Multihull craft should meet the relevant requirements of annex 7 for all permitted cases of loading.

2.3.3 Subject to 2.3.4, all other craft should meet the following criteria in all permit ted conditions of loading: .1 resolution A.562(14) (weather criterion); W/1576n/pp/EWP R ESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFE TY FOR HIGH SPEED CRAFT MSC 63/23/Add.2 ANNEX 18 Page 28 .2 the area under the righting lever curve (GZ curve) should not be less than 0.07 m.rad up to e = 15° when the maximum righting lever (GZ) occurs at e = 15° and 0.055 m.rad up to e = 30° when the maximum rig hting lever occurs at e = 30° or above.

Where the maximum righting lever occurs at angles of between e = 15° and e = 30°, the co rresponding area under the righting lever curve should be: A = 0.055 + 0.001 (30° - emax) (m.rad) where: emax is the angle of heel in degrees at which the righting lever curve reaches its maximum; .3 the area under the righting lever curve between e = 30° and e = 40° or between e = 30° and the angle of flooding - where: emax is the angle of heel in d egrees at which the righting lever curve reaches its maximum; .3 the area under the righ ting lever curve between e = 30° and e = 40° or between e = 30° and the angle of floodin g ef *, if this angle is less than 40°, should not be less than 0.03 m.rad; .4 the right ing lever GZ should be at least 0.20 m at an angle of heel equal to or greater than 30°; .5 the maximum righting lever should occur at an angle of heel not less than 15°; and .6 the initial metacentric height GMo should not be less than 0.15 m.

2.3.4 Where the characteristics of the craft are unsuitable for application of 2.3.3, th e Administration may accept alternative criteria equivalent to those stipulated in 2.3.3 , appropriate to the type of craft and area of operation.

2.4 Intact stability in the non - displacement mode 2.4.1 The requirements of this secti on and section 2.12 should be applied on the assumption that any stabilization systems f itted are fully operational.

2.4.2 Suitable calculations should be carried out and/or tests conducted to demonstrate that, when operating in the non-displacement and - on the assumption that any stabilizat ion systems fitted are fully operational.

2.4.2 Suitable calculations should be carried out and/or tests conducted to demonstrate that, when operating in the non-displacement and transient modes within approved operati onal limitations, the craft will, after a disturbance causing roll, pitch, heave or heel due to turning or any combination thereof, return to the original attitude.

2.4.3 The roll and pitch stability on the first and/or any other craft of a series shoul d be qualitatively assessed during operational safety trials as required by chapter 18 a nd annex 8.

The results of such trials may indicate the need to impose operational limitations.

In applying this criterion, small openings through which progressive flooding cannot tak e place need not be considered as open.

WIl576n/pp/EWP RESOLUTION MS