The exposed surfaces of vapour barriers and adhesives used in conjunction with insulatio n materials should have low flame-spread characteristics.

Furniture and furnishings in public spaces and crew accommodation should comply with the following standards: .1 all case furniture is constructed entirely of approved non-combu stible or fire-restricting materials, except that a combustible veneer with a calorific value not exceeding 45 MJ/m 2 may be used on the exposed surface of such articles; .2 al l other furniture such as chairs, sofas and tables is constructed with frames of non-com bustible or fire-restricting materials; .3 all draperies, curtains and other suspended t extile materials have qualities of resistance to the propagation of flame in accordance with standards* developed by the Organization; Refer to the Recommendation on test metho d for determining the resistance to flame of vertically supported textiles and films, ad opted by the Organization by resolution A.47l(XII), and amendments to the recommendation adopted by resolution A.563(14).

W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO NAL CODE OF SAFETY - Organization by resolution A.47l(XII), and amendments to the recomm endation adopted by resolution A.563(14).

W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO NAL CODE OF SAFETY FOR HIGH SPEED CRAFT 7.4.3.4 7.4.3.5 7.4.3.6 7.4.3.7 7.4.3.8 MSC 63/2 3/Add.2 ANNEX 18 Page 61 .4 all upholstered furniture has qualities of resistance to the ignition and propagation of flame in accordance with standards* developed by the Organiz ation; .5 all bedding components comply with the standards** developed by the Organizati on; and .6 all deck finish materials comply with the standards*** developed by the O~gan ization.

The following surfaces should, as a minimum standard be constructed of materials having low flame-spread characteristics: .1 exposed surfaces in corridors and stairway enclosur es, and of bulkheads, wall and ceiling linings in all accommodation and service spaces a nd control stations; .2 concealed or inaccessible spaces in accommodation, service space s and control stations.

Any thermal and acoustic insulation material, if not in compliance with 7.2.1 or 7.2.2, should be of non-combustible material.

- .2 concealed or inaccessible spaces in accommodation, service spaces and control stati ons.

Any thermal and acoustic insulation material, if not in compliance with 7.2.1 or 7.2.2, should be of non-combustible material.

Materials used in the craft, when exposed to fire, should not emit smoke or toxic gases in quantities that could be dangerous to humans as determined in tests of a standard dev eloped by the Organization.

Void compartments, where low density combustible materials are used to provide buoyancy, should be protected from adjacent fire hazard areas by fire-resisting divisions, in acco rdance with tables 7.4-1 and 7.4-2.

Also, the space and closures to it should be gastight but it should be ventilated to atm osphere.

In compartments where smoking is allowed, suitable non-combustible ash containers should be provided.

In compartments