operating in the COSPAS-SARSAT system).

W/1687n/pp/EWP (RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNAT IONAL CODE OF SAFETY FOR HIGH SPEED CRAFT (Footnote continued) MSC 62/23/Add.2 ANNEX 18 Page 143 .8 Resolution A.697(17): Performance standards for survival craft radar transpo nders for use in search and rescue operations • .

9 Resolution A.612(15): Performance standards for float-free VHF emergency position-indi cating radio beacons .

.

10 Resolution A.663(16): Performance standards for INMARSAT Standard-C ship earth statio ns capable of transmitting and rece~v~ng direct-printing communications and resolution A .570(14): Type approval of ship earth stations .

.

11 Resolution A.664(16): Performance standards for enhanced group call equipment .

.

12 Resolution A.661(16): Performance standards for float-free satellite emergency positi on-indicating radio beacons operating through the geostationary INMARSAT satellite syste m on 1.6 GHz • .

13 Resolution A.662(16): Performance standards for float-free release and activation arr angements for emergency radio equipment .

.

14 Resolution A.699(17): System performance standard for the - .

13 Resolution A.662(16): Performance standards for float-free release and activation arr angements for emergency radio equipment .

.

14 Resolution A.699(17): System performance standard for the promulgation and co-ordinat ion of maritime safety information using high-frequency narrow-band direct-printing .

.

15 Resolution A.700(17): Performance standards for narrow-band direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent infor mation to ships (MSI) by HF.

W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO NAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2 ANNEX 18 Page 144 14.14 14.14.1 14.14.2 14.14.3 14.14.4 14.14.5 14 .14.6 14.14.1 14.14.8 Maint e nance requ irements Equ ipment should be so designed that the main units can be replaced readily without elabora te recalibration or readjustment.

Where applicable, equipment should be so constructed and installed that it is readily ac cessible for inspection and on-board maintenance purposes.

Adequate information should be provided to enable the equipment - Where applicable, equi pment should be so constructed and installed that it is readily accessible for inspectio n and on-board maintenance purposes.

Adequate information should be provided to enable the equipment to be properly operated and maintained, taking into account the recommendations of the Organization*.

Adequate tools and spares should be provided to enable equipment to be maintained .

The Administration should ensure that radio equipment required by this chapter is mainta ined to provide the availability of the functional requirements specified in 14.4 and to meet the recommended performance standards of such equipment.

On crafts engaged on voyages in sea areas Al and A2, the availability should be ensured by using such methods as duplication of equipment, shore-based maintenance or at-sea ele ctronic maintenance capability, or