Functional requirements Every craft, while at sea, should be capable: .1 except as provi
ded in 14.7.1.1 and 14.9.1.4.3, of transmitting ship-to-shore distress alerts by at leas
t two separate and independent means, each using a different radiocommunication service;
.2 of receiving shore-to-ship distress alerts; .3 of transmitting and receiving ship-to-
ship distress alerts; .4 of transmitting and receiving search and rescue co-ordinating c
ommunications; .5 of transmitting and receiving on-scene communications; .6 of transmitt
ing and, as required by 13.5, receiving signals for locating~; .7 of transmitting and re
ceiving** marine safety information; .8 of transmitting and receiving general radiocommu
nications to and from shore-based radio systems or networks subject to 14.14.8; and .9 o
f transmitting and receiving bridge-to-bridge communications.

* Refer to resolution A.614(15) on carriage of radar operating in the frequency band 9,3
00-9,500 MHz adopted by the Organization.

** It should be noted that craft may have a need for reception of certain maritime safet
y information while in port.

W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) - frequency band 9,300-9,5
00 MHz adopted by the Organization.

** It should be noted that craft may have a need for reception of certain maritime safet
y information while in port.

W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO
NAL CODE OF SAFETY FOR HIGH SPEED CRAFT 14.5 14.5.1 14.5.2 14.5.3 14.6 14.6.1 Radio inst
allations MSC 62/23/Add.2 ANNEX 18 Page 133 Every craft should be provided with radio in
stallations capable of complying with the functional requirements prescribed by 14.4 thr
oughout its intended voyage and, unless exempted under 14.3, complying with the requirem
ents of 14.6 and, as appropriate for the sea area or areas through which it will pass du
ring its intended voyage, the requirements of either 14.7, 14.8, 14.9 or 14.10.

Every radio installation should: .1 be so located that no harmful interference of mechan
ical, electrical or other origin affects its proper use, and so as to ensure electromagn
etic compatibility and avoidance of harmful interaction with other equipment and systems
; .2 be so located as to ensure the greatest possible degree of safety and operational a
vailability; - as to ensure electromagnetic compatibility and avoidance of harmful inter
action with other equipment and systems; .2 be so located as to ensure the greatest poss
ible degree of safety and operational availability; .3 be protected against harmful effe
cts of water, extremes of temperature and other adverse environmental conditions; .4 be
provided with reliable, permanently arranged electrical lighting, independent of the mai
n sources of electrical power, for the adequate illumination of the radio controls for o
perating the radio installation; and .5 be clearly marked with the call sign, the ship s
tation identity and other codes as applicable for the use of the radio installation.

Coritrol of the VHF radiotelephone channels, required for navigational safety, should be
immediately available on the navigating bridge convenient to the conning