.2 concealed or inaccessible spaces in accommodation, service spaces and control station s.

Any thermal and acoustic insulation material, if not in compliance with 7.2.1 or 7.2.2, should be of non-combustible material.

Materials used in the craft, when exposed to fire, should not emit smoke or toxic gases in quantities that could be dangerous to humans as determined in tests of a standard dev eloped by the Organization.

Void compartments, where low density combustible materials are used to provide buoyancy, should be protected from adjacent fire hazard areas by fire-resisting divisions, in acco rdance with tables 7.4-1 and 7.4-2.

Also, the space and closures to it should be gastight but it should be ventilated to atm osphere.

In compartments where smoking is allowed, suitable non-combustible ash containers should be provided.

In compartments where smoking is not allowed, adequate notices should be displayed.

* Refer to the Recommendation on fire test procedures for upholstered furniture, adopted by the Organization by resolution A.652(16).

** Refer to the Recommendation on fire test procedures for ignitability of - * Refer to the Recommendation on fire test procedures for upholstered furniture, adopted by the Org anization by resolution A.652(16).

** Refer to the Recommendation on fire test procedures for ignitability of bedding compo nents, adopted by the Organization by resolution A.688(17).

*** Refer to the Recommendation on improved fire test procedures for surface flammabilit y of bulkhead, ceiling and deck finish materials, adopted by the Organization by resolut ion A.653(16) and the Recommendation on fire test procedures for ignitability of primary deck coverings, adopted by the Organization by resolution A.687(16).

W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO NAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2 ANNEX 18 Page 62 7.4.3.9 The exh aust gas pipes should be arranged so that the risk of fire is kept to a minimum.

To this effect, the exhaust system should be insulated and all the compartments and stru ctures which are contiguous with the exhaust system, or those which may be affected by i ncreased temperatures caused by waste gases in normal operation or in an emergency, shou ld be constructed of non-combustible - contiguous with the exhaust system, or those whic h may be affected by increased temperatures caused by waste gases in normal operation or in an emergency, should be constructed of non-combustible material or be shielded and in sulated with non-combustible material to protect from high temperatures.

7.4.3.10 The design and arrangement of the exhaust manifolds or pipes should be such as to ensure the safe discharge of exhaust gases.

7.4.4 Arrangement 7.4.4.1 Internal stairways which serve more than two decks of accommod ation should be enclosed at all levels with smoke-tight divisions of non-combustible or fire-restricting materials, and where only two decks are served, such enclosures should be provided on at least one level.

Stairways may be fitted in the open in a public space, provided they lie wholly within s uch public space.

7.4.4.2 L